



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

836 *PUSH-LOK Plus*
Multipurpose – High Temperature



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp	Field Attachable
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	HY Series	82 Series
836-4	1/4	6,3	0.50	12,7	400	2,8	2-1/2	65	0.09	0,13	•	•
836-6	3/8	10	0.63	15,9	400	2,8	3	75	0.11	0,16	•	•
836-8	1/2	12,5	0.78	19,8	400	2,8	4	125	0.18	0,27	•	•
836-10	5/8	16	0.91	23,0	350	2,4	5	150	0.19	0,28	•	•
836-12	3/4	19	1.03	26,2	300	2,1	6	180	0.24	0,36	•	•

- Field Attachable Assembly Instructions are in Section B with each Fitting Series.
- Push-Lok is not recommended for any fuel, refrigerant, or for use in air conditioners and heat pump applications.
- Push-Lok is not recommended for applications where extreme pulsation is encountered.
- See Section B for Assembly Instructions.
- Temperature Range of other media listed in Section E.

Application: Pneumatic, petroleum base hydraulic fluid, lubricating oils, diesel fuels and antifreeze solutions.

Inner Tube: PKR*

Reinforcement: One fiber braid.

Cover: Blue neoprene or PKR, MSHA accepted

Temperature Range:

Air: +212°F (+100°C)

Water: +185°F (+85°C)

Oil: -55°F to +302°F
 (-48°C to +150°C).

Diesel fuels: -40°C to 150°C
 (-40°F to 302°F) with HY crimps only