



WEST MICHIGAN RUBBER & SUPPLY

1.800.533.9677

sales@westmichiganrubber.com

T505OG - 240 PSI XLPE Tube Chemical Hose



**WARNING
BEFORE USING
CHEMICAL HOSES
CONSULT CHEMICAL
RESISTANCE CHART
OR CONSULT
FACTORY.**

APPLICATION

Suction and transfer service for a variety of chemicals and solvents. Will handle 90% of existing chemicals. See Chemical Resistance Chart on pages 58 – 66.

COVER

Green EPDM — abrasion and ozone resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Transparent XLPE (cross-linked polyethylene).

TEMPERATURE RANGE

Normal recommended operating temperature is -4°F (-20°C) to 150°F (+65°C).

STANDARD LENGTH

100 feet

BRANDING

ALFAGOMMA – ITALY T505 16 BAR (240 PSI) – XLPE
CHEMICAL – S & D (in orange letters)

NOTE — Can be sterilized with water and 5% soda mix

IT IS ADVISABLE TO TEST THE TUBE MATERIAL UNDER ACTUAL SERVICE
CONDITIONS PRIOR TO USE.

NOTE: FOR MAXIMUM SERVICE LIFE, WE RECOMMEND THAT T505 HOSE BE
FLUSHED OUT AFTER EVERY USE.

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T505OG075	3/4	19	1.22	31	46	240	7 1/2
T505OG100	1	25	1.46	37	57	240	9
T505OG150	1 1/2	38	2.01	51	78	240	13 1/4
T505OG200	2	51	2.56	65	103	240	16 1/4
T505OG300	3	76	3.62	92	187	240	20 3/4
T505OG400	4	102	4.65	118	254	240	26 1/2