























Pipe Fittings and Port Adapters





The Fitting Authority


Nipples	F50HAO SAE-ORB / SAE-ORB  G11	F5OF SAE-ORB / NPTF  G11	FF NPTF / NPTF  G11	FFF NPTF / NPTF Long  G11	FF33M BSPT / BSPT  G12
Couplings	G5HG5 SAE-ORB / SAE-ORB  G12	GG NPTF / NPTF  G12	GG44M BSPP / BSPP  G12	Reducers, Expanders, Conversions	F5OG5 SAE-ORB / SAE-ORB  G13
F5OG SAE-ORB / NPTF  G13	F5OHG8 SAE-ORB / Metric  G13	F5OHG4 SAE-ORB / BSPP  G13	FHG5 NPTF / SAE-ORB  G14	FG NPTF / NPTF  G14	PTR Pipe Thread Reducer  G14
FHG8 NPTF / Metric  G14	FHG4 NPTF / BSPP  G15	F870HG87 ISO 6149 / ISO 6149  G15	F8OHG5 Metric-ORR / SAE-ORB  G15	F8OHG Metric-ORR / NPTF  G15	F4OHG5 BSPP-ORR / SAE-ORB  G16
F4OHG BSPP-ORR / NPTF  G16	PTR34 BSPT / BSPP  G16	RI-ED BSPP-ED / BSPP  G17	RI BSPP-CF / BSPP  G18	F3HG BSPT/ NPTF  G19	F3HG5 BSPT / SAE-ORB  G19
45° Elbows	CD45 NPTF / NPTF  G19	DD45 NPTF / NPTF  G19	90° Elbows	AOEG5 SAE-ORB / SAE-ORB  G19	AOEG SAE-ORB / NPTF  G19
AOE4G SAE-ORB / NPTF Long  G20	CR NPTF / NPTF  G20	CD NPTF / NPTF  G20	DD NPTF / NPTF  G20	A87LPOEG87LPM ISO 6149 / ISO 6149  G21	A4OEG4M BSPP-ORR / BSPP  G21
Tees	G5G5JAO SAE-ORB Branch Tee  G21	AOG5JG5 SAE-ORB Run Tee  G22	G5G5JG5 SAE-ORB Tee  G22	RRS NPTF Tee  G22	MMS NPTF Branch Tee  G22

MRO NPTF Run Tee 	MMO NPTF Tee 	MMO444 BSPP Tee 	Cross	KMMOO NPTF Cross 	
G22	G23	G23		G23	
Plugs, Bleed Adapters	P5ON SAE-ORB Hex Head 	HP5ON SAE-ORB Hollow Hex 	HP NPTF Hex Head 	SHP NPTF Square Head 	HHP NPTF Hollow Hex Head 
G23	G24	G24	G24	G24	G24
HPC NPTF Pipe Cap 	P87OMN ISO 6149 Hex Head 	VSTI M-OR ISO 6149 Hollow Hex 	VSTI M-ED Metric-ED Hollow Hex 	VSTI R-ED BSPP-ED Hollow Hex 	P47OMN BSPP-ORB Hex Head 
G25	G25	G25	G25	G26	G26
HP3M BSPT Hex Head 					
G26					

Diagnostic, Orifice and Bleed Adapters (Shown in Section N)

Bleed Adapters	P5ONBA Bleed Screw / Bleed Adapter 	HPBA Bleed Screw / NPT 
	N12	N12

O-Rings and Seals (Shown in Section O)

O-Rings and Seals	SAE O-Ring  O3	ISO 6149 O-Ring  O4	Metric O-Ring  O4	Metric Retaining Ring  O4	BSPP O-Ring  O5
BSPP Retaining Ring 					
O5					

Introduction

This Section contains adapters with thread types including: NPT, NPTF, BSPT, BSPP, SAE UN/UNF, and Metric. All the threads in this section are made to industry specifications with conformance shown in Table G1.

Design and Construction

Shaped products (elbows, tees and crosses) are hot forged and machined, while straights are manufactured from cold drawn barstock. Where applicable, these products are made in conformance with the design criteria of the Society of Automotive Engineers Standards, SAE J514, J530.

Parker Fluid Connector products made from steel and brass, for the most part, have NPTF threads. Stainless steel products may have NPT or slightly modified NPT threads to minimize the chance of galling on assembly.

Standard Material Specifications: The standard materials used in the manufacture of Industrial Pipe and Adapter fittings are shown in Table G2.

Note: Upon request, pipe fittings, adapters and plugs could be furnished in materials other than those shown in the material specifications chart.

Finish - Zinc plating with yellow chromate (being changed to zinc chromium 6 free) is used on all standard steel products. Stainless steel fittings are passivated.

Assembly and Installation

Please refer to [Section T](#) for the assembly and installation instructions for Pipe Fittings and Port Adapters.

Thread	Standard
NPT	ANSI B1.20.1, FED-STD-H28/7
NPTF	SAE J476, ANSI B1.20.3, FED-STD-H28/8
BSPT	BS 21, ISO 7/1
BSPP	BS 2779, ISO 228/1
Metric	ISO 261, ANSI B1.13M, FED-STD-H28/21
UN/UNF*	ANSI B1.1, FED-STD-H28/2

*Class 2A or 2B

Table G1 — Thread Conformance Standards

Pipe Fittings, Adapters and Plugs	Steel		Stainless Steel		Brass	
	ASTM	Type	ASTM	Type	ASTM	Type
Forged Bodies	A576	1214/1215	A182	316	B124	CA377
Bar Stock Bodies	A108	12L14	A479	316	B16 B453	CA360 CA345
Cold Formed Bodies	A576	C1010 / C1008	—	—	—	—

Table G2 — Standard Material Specifications for Industrial Pipe Fittings and Adapters

How Port Connections Work

Tapered (“Pipe”) Threads

There are three types of tapered threads commonly used in industrial applications.

- NPT/NPTF
- BSPT
- Metric Taper

All three thread styles noted above use the same basic metal-to-metal sealing design for achieving a seal. Although very similar, there are differences in the thread dimensions, pitch, and flank angle that do not allow interchangeability.

NPT / NPTF Threads

NPT threads, when assembled without a sealant, leave a spiral leak path at the crest-root junction as shown in Fig. G1. To seal pressurized fluid, NPT threads require a suitable sealant. NPTF threads (Dryseal), on the other hand, when assembled, do not leave the spiral leak path. This is because they have controlled truncation at the crest and root, ensuring metal-to-metal crest-root contact prior to, or just as the male-female thread flanks make contact as seen in Fig. G2. Upon further tightening, the thread crests are flattened out until the flanks also make metal-to-metal contact as seen in Fig. G3. Thus, theoretically at least, there is no passage left for the fluid to leak, provided all surfaces are flawless and dimensions exact. **In reality, this is not the case and a sealant/lubricant is necessary to achieve a leak free joint, even with NPTF threads.** The sealant/lubricant fills all imperfections in the surfaces affecting the seal and also provides lubrication to ease assembly and minimize galling.

Dimensions and pressures for reference only, subject to change.




Fig. G1 — NPT: Wrench Tight, No Crest-Root Contact, Flank Contact Only




Fig. G2 — NPTF: Hand Tight, Crest to Root Contact




Fig. G3 — NPTF: Wrench Tight, Crest to Root and Flank Contact

Application Guidelines for Tapered Threads

Straight Connectors with NPT/NPTF 3/4-14 and Smaller

Straight connectors with 3/4-14 NPT/NPTF and smaller male pipe threads have very high pressure holding capability and seal reliability when used in applications without "make and break" (such as maintenance) requirements.

They are also well suited for low cycle non-pulsating (static) applications with pressures in excess of 6,000 psi.

Straight Connectors with NPT/NPTF above 3/4 -14 and All Shaped Connectors with NPT/NPTF Threads

It is difficult to always tighten shapes with pipe threads to an optimum tightness level because of orientation requirements. Also, all connectors in this category with pipe threads have low reliability for leak free operation in dynamic applications. Therefore, they are not preferred where a leak free joint is required.

All NPTF Connectors

While a pipe thread connection can be disassembled and re-assembled in low-pressure systems, it is not intended to be a frequently assembled and disassembled connection. (When connectors are known to be disassembled and re-assembled repeatedly, pipe connections are not preferred for high-pressure systems.)

For the above applications, a port connection with an elastomeric seal, such as SAE straight thread port (SAE J1926/ISO11926), SAE four bolt split flange (SAE J518/ISO 6162), and ISO 6149 is recommended. For applications where elastomeric seals can't be used, consult the manufacturer.

As noted, BSPT and metric taper are designed and perform similarly. Follow the NPT/NPTF guidelines for their application.

In general, tapered thread connections have the following limitations which should be considered when specifying port connections:

- Poor dynamic sealing characteristics
- Possible expansion, and even cracking, of the port
- Orientation is a concern in shaped connectors
- Larger threads are more prone to leakage because of more potential leak points
- System contamination due to thread sealant
- Prone to galling, especially in stainless steel
- Limited remakeability

Parallel Thread Adapters

Straight, or parallel, thread ports in various forms are becoming more popular in hydraulic systems because they are more reliable and easier to service.

Three types of threads are used for parallel thread ports:

- UN/UNF (SAE straight thread)
- BSPP (British Standard Pipe, Parallel)
- Metric parallel

Because parallel threads only serve one function (i.e. holding the fitting in place), some other means of sealing is always present, such as an elastomeric O-ring or a metal seal. There are many variations of sealing methods, and in some cases, they are interchangeable among the different thread forms and may appear to be similar.

UN / UNF Threads

SAE J1926 uses UN/UNF threads and is often referred to as SAE Straight Thread. The female port is often referred to as ORB or O-ring boss. This port style, shown in Fig. G4, is widely used in North America.




Fig. G4 — Typical O-Ring Boss Port

BSPP

In Europe, Japan and many other former Commonwealth nations, the British Standard Pipe thread form, BSP, is still used extensively to connect pipes and components in hydraulic systems. The BSP thread is offered in a straight (parallel) form known as BSPP and a tapered form known as BSPT. These threads feature a 55° flank angle. Fittings in this section with male BSPP threads use a primary sealing method of an O-ring and retaining ring, as shown in Fig. G5.




Fig. G5 — O-Ring with Retaining Ring

Additional sealing methods such as a cutting face or an EOLastic seal, as shown in Fig. G6, are also available on other fittings within the catalog. These BSPP fittings are all designed to thread into a female BSPP port (ISO 1179), however, the seal is created with one of the aforementioned sealing methods, not with the threads. It is also important to note that with these BSPP threaded connections, the seal occurs on the port surface, or spotface, not in an O-ring gland or chamfer as SAE and ISO-6149 straight thread do. A detail of the BSPP port is shown on page U29.




Fig. G6 — O-Ring in Fitting Groove

Dimensions and pressures for reference only, subject to change.

Metric Parallel

In Europe, primarily in Germany, the traditional metric parallel thread form is used extensively to connect components in hydraulic systems. This metric thread is designed to thread into and seal in a female Metric parallel port conforming to ISO 9974-1 (DIN-3852, Part 1). Fittings in this section with male metric threads use a primary sealing method of an O-ring and retaining ring (similar to Fig. G5). Additional sealing methods such as a cutting face or an EOlastic seal (similar to Fig. G6) are also available on other fittings within the catalog. Sealing is accommodated with one of the aforementioned sealing methods, not with the threads. It is also important to note that with these male metric threads, the seal occurs on the top face (spotface) of the port, not in an O-ring gland or chamfer as in SAE and ISO-6149 straight threads. A detail of this metric port is shown on [page U25](#).

To minimize further proliferation of additional port thread styles, the International Standards Organization Technical Committee 131 completed the development of a world standard leak-free port connection. It is recommended that this port, ISO 6149-1, be specified in all new hydraulic fluid power applications.

Parker and other fluid connector manufacturers have expanded product offering to incorporate the ISO 6149 male studs as a standard on many tube fitting products. Parker offers the ISO 6149 male stud end, shown in Fig. G7, on several tube fitting products including: Seal-Lok, Triple-Lok, EO, EO-2, Conversion Adapters, Plugs, etc. This port, utilizes metric parallel threads for mechanical holding power and a sealing method similar to the proven SAE Straight Thread O-ring port. A detail of this metric port is shown on [page U26](#).





Fig. G7 — ISO 6149 Male

Feature	Advantage	Benefit
Tapered Thread Fittings		
Compact size	Suitable selection for plumbing in limited or tight space in a compact system.	Compact systems are more efficient and reduce the need for excessive routing of costly hose or tube
Widespread acceptability	Available worldwide for OEM and MRO applications	Eases efforts to find component parts and replacement fittings, reducing unnecessary downtime
High static pressure rating	Allows for use in high pressure applications	Increases versatility of fitting
Offered in three standard materials (Steel, Stainless Steel, and Brass)	Allows customer to match media and temperature applications without special fittings and seals.	Reduces component procurement costs and increases fitting availability
Adaptable to ORFS, Flareless Bite-type, Metric Bite-type, 37° flare, etc.	Versatility for end customer and for customer standardization efforts	Standardization reduces procurement costs
High temperature applications	Is not limited by temperature range of elastomeric seal	Increases versatility of fitting
Straight Thread Fittings		
Reliable sealing in dynamics applications	Ideal in systems with high pressure and cycling	Provides reliable, long-term sealing
Unlimited reusability/ remakeability	Extends the service life of the fitting	Reduces maintenance costs and component replacement costs
No thread sealant needed	Eliminates the potential for contaminating and damaging sensitive hydraulic components due to thread sealant	Reduces maintenance costs and component replacement costs
Infinite positioning of shaped adapters	Eliminates potential of damaging adapter and/or component by incorrectly assembling to accomplish correct orientation	Improves assembly time and reduces maintenance costs
Elastomeric seal	Tolerant of minor surface imperfections to provide leak-free connection	Reduces operational and maintenance costs

Dimensions and pressures for reference only, subject to change.

Port Ends for SAE J1926-1 (ISO 11926-1) Port






	Thread	Locknut Hex	Drill	Minimum Thread	Stud Length	
SIZE	T UN/UNF	C4 (inch)	D Max (inch)	L4 Min (inch)	X (inch)	Z Max (inch)
LIGHT DUTY (TRIPLE-LOK, FERULOK, ADAPTERS)						
2	5/16-24	7/16	0.063	0.390	0.297	0.36
3	3/8-24	1/2	0.125	0.390	0.297	0.33
4	7/16-20	9/16	0.172	0.454	0.360	0.39
5	1/2-20	5/8	0.234	0.454	0.360	0.43
6	9/16-18	11/16	0.297	0.500	0.391	0.43
8	3/4-16	7/8	0.391	0.562	0.438	0.49
10	7/8-14	1	0.484	0.656	0.500	0.56
12	1 1/16-12	1 1/4	0.609	0.750	0.594	0.65
14	1 3/16-12	1 3/8	0.719	0.750	0.594	0.65
16	1 5/16-12	1 1/2	0.844	0.750	0.594	0.65
20	1 5/8-12	1 7/8	1.078	0.750	0.594	0.65
24	1 7/8-12	2 1/8	1.312	0.750	0.594	0.65
32	2 1/2-12	2 3/4	1.781	0.750	0.594	0.59
HEAVY DUTY (SEAL-LOK)						
2	5/16-24	1/2	0.063	0.390	0.374	0.38
3	3/8-24	9/16	0.125	0.390	0.374	0.39
4	7/16-20	5/8	0.172	0.454	0.433	0.43
5	1/2-20	11/16	0.236	0.454	0.433	0.44
6	9/16-18	3/4	0.264	0.500	0.472	0.47
8	3/4-16	15/16	0.378	0.562	0.551	0.54
10	7/8-14	1 1/16	0.484	0.656	0.630	0.63
12	1 1/16-12	1 3/8	0.609	0.750	0.728	0.73
14	1 3/16-12	1 1/2	0.709	0.750	0.728	0.73
16	1 5/16-12	1 5/8	0.811	0.750	0.728	0.73
20	1 5/8-12	1 7/8	1.024	0.750	0.728	0.73
24	1 7/8-12	2 1/8	1.260	0.750	0.728	0.73
32	2 1/2-12	2 3/4	1.575	0.750	0.728	0.73

1) See [page O3](#) for SAE O-rings.

2) See [page U26](#) for port details.

Dimensions and pressures for reference only, subject to change.

Port Ends for ISO 6149-1 Port




SIZE	Thread	Drill	Minimum Thread	Stud Length		Lockhead Hex
	T87 Metric	D Max (mm)	L4 Min (mm)	L1 (mm)	L2 Max (mm)	S3 (mm)
LIGHT DUTY (TRIPLE-LOK, FERULOK, ADAPTERS)						
M8	M8X1	3	10.0	8.5	8.7	12
M10	M10X1	4.5	10.0	8.5	8.7	14
M12	M12X1.5	6	11.5	11.0	11.1	17
M14	M14X1.5	7.5	11.5	11.0	11.1	19
M16	M16X1.5	9	13.0	11.5	11.6	22
M18	M18X1.5	11	14.5	12.5	12.6	24
M20	M20X1.5	—	14.5			—
M22	M22X1.5	14	15.5	13.0	13.0	27
M27	M27X2	18	19.0	16.0	16.0	32
M30	M30X2	—	19.0			—
M33	M33X2	23	19.0	16.0	16.0	41
M38	M38X2	—	19.0			—
M42	M42X2	30	19.5	16.0	16.0	50
M48	M48X2	36	22.0	17.5	17.3	55
M60	M60X2	44	24.5	17.5	17.3	65
HEAVY DUTY (SEAL-LOK)						
M8	M8X1	2	10.0	9.5	9.7	12
M10	M10X1	3	10.0	9.5	9.7	14
M12	M12X1.5	4	11.5	11.0	11.1	17
M14	M14X1.5	6	11.5	11.0	11.1	19
M16	M16X1.5	7	13.0	12.5	12.6	22
M18	M18X1.5	9	14.5	14.0	14.1	24
M20	M20X1.5	11	14.5	14.0		—
M22	M22X1.5	12	15.5	15.0	15.0	27
M27	M27X2	15	19.0	18.5	18.0	32
M30	M30X2	18	19.0	18.5	18.5	36
M33	M33X2	20	19.0	18.5	18.5	41
M38	M38X2	26	19.0	18.5	19.0	46
M42	M42X2	26	19.5	19.0	19.0	50
M48	M48X2	32	22.0	21.5	21.5	55
M60	M60X2	40	24.5	24.0	24.0	65

1) See page O4 for ISO 6149 O-rings.


2) See page U25 for port details.

Dimensions and pressures for reference only, subject to change.

NPTF and BSPT Port Ends



**NPTF and BSPT
Port**




**NPTF and BSPT
Stud**

	Thread	Drill	Minimum Thread	Thread Engagement
SIZE	PT	D Max (inch)	J (inch)	TE (inch)
NPTF				
2	1/8-27	0.188	0.31	0.24
4	1/4-18	0.281	0.44	0.34
6	3/8-18	0.406	0.47	0.34
8	1/2-14	0.531	0.59	0.46
12	3/4-14	0.719	0.63	0.46
16	1-11 1/2	0.938	0.75	0.59
20	1 1/4-11 1/2	1.250	0.78	0.59
24	1 1/2-11 1/2	1.500	0.81	0.59
32	2-11 1/2	1.938	0.81	0.59
BSPT				
2	1/8-28	0.188	0.31	0.24
4	1/4-19	0.281	0.44	0.34
6	3/8-19	0.406	0.47	0.34
8	1/2-14	0.531	0.59	0.46
12	3/4-14	0.719	0.63	0.46
16	1-11	0.938	0.75	0.59
20	1 1/4-11	1.250	0.78	0.59
24	1 1/2-11	1.438	0.81	0.59
32	2-11	1.938	0.81	0.59

Dimensions and pressures for reference only, subject to change.

Port Ends for ISO 9974-1 and 1179-1 Ports

**ISO 9974**

Thread	O-Ring, RR Stud	Light Duty (L Series)	Heavy Duty (S Series)	Port Min Depth	ED Stud	O-Ring, RR Non- Adj Stud	O-Ring, RR Adj- Stud	O-Ring, RR Adj-Stud, Locknut Hex	Dowty Seal Stud	Cutting Face Stud	
	Drill Max					L2 (mm)	L4 (mm)	L6 (mm)	L7 (mm)	S2 (mm)	L8 (mm)
M8	M8X1	2	—	—	8	—	8.0	8.6	11	—	8
M10	M10X1	4	4	—	8	8	8.0	8.7	14	—	8
M12	M12X1.5	5	6	4	12	12	8.7	10.0	17	—	12
M14	M14X1.5	7	7	5	12	12	8.7	10.0	19	—	12
M16	M16X1.5	9	9	7	12	12	9.0	11.3	21	—	12
M18	M18X1.5	11	11	8	12	12	11.0	12.2	22	—	12
M20	M20X1.5	11	-	10	14	14	12.7	—	—	—	14
M22	M22X1.5	13	14	12	14	14	12.7	13.7	27	—	14
M26	M26X1.5	13	18	—	16	16	14.0	—	—	—	16
M27	M27X2	16	—	16	16	16	15.0	16.8	32	—	16
M33	M33X2	22	23	20	18	18	15.0	16.8	38	—	18
M42	M42X2	28	30	25	20	20	15.5	17.3	48	—	20
M48	M48X2	36	36	32	22	22	19.5	19.3	55	—	22
M60	M60X2	44	—	—	24.5	—	20.5	22.3	65	—	—

ISO 1179

Thread	O-Ring, RR Stud	Light Duty (L Series)	Heavy Duty (S Series)	Port Min Depth	ED Stud	O-Ring, RR Non- Adj Stud	O-Ring, RR Adj- Stud	O-Ring, RR Adj-Stud, Locknut Hex	Dowty Seal Stud	Cutting Face Stud	
	Drill Max					L2 (mm)	L4 (mm)	L6 (mm)	L7 (mm)	S2 (mm)	L8 (mm)
2	1/8-28	4.4	4	—	8	8	6.3	7.2	14	8	8
4	1/4-19	7.5	7	5	12	12	9.4	9.4	19	11	12
6	3/8-19	9.9	9	8	12	12	9.4	9.3	22	12	12
8	1/2-14	12.3	14	12	14	14	12.6	13.1	30	14	14
12	3/4-14	15.5	18	16	16	16	12.6	13.1	36	16	16
16	1-11	21.5	23	20	18	18	16.0	14.7	46	16	18
20	1-1/4-11	27.5	30	25	20	20	16.0	14.7	50	19	20
24	1-1/2-11	33.0	36	32	22	22	16.0	14.7	55	22	22
32	2-11	—	—	—	26	—	16.0	14.7	75	25	—

1) See [Section O](#) for O-rings and seals.

2) O-ring with retaining ring stud ends are not shown in ISO 9974.


3) See [page U30](#) for ISO 9974-1 port details.4) See [page U29](#) for ISO 1179-1 port details.

Dimensions and pressures for reference only, subject to change.

F50HAO

Straight Thread Union
SAE-ORB / SAE-ORB


HPD Base # 0505



TUBE FITTING PART #	END SIZE		C4 HEX (in.)	L1 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2A	2 UN/UNF-2A			-S	-SS	-B
4 F50HAO	7/16-20	7/16-20	9/16	1.27	6.0	6.0	
6 F50HAO	9/16-18	9/16-18	11/16	1.41	6.0	6.0	
8 F50HAO	3/4-16	3/4-16	7/8	1.56	6.0	6.0	
10 F50HAO	7/8-14	7/8-14	1	1.81	5.0	5.0	
12 F50HAO	1 1/16-12	1 1/16-12	1 1/4	2.13	5.0	5.0	
16 F50HAO	1 5/16-12	1 5/16-12	1 1/2	2.13	4.0	4.0	
20 F50HAO	1 5/8-12	1 5/8-12	1 7/8	2.13	4.0	4.0	
24 F50HAO	1 7/8-12	1 7/8-12	2 1/8	2.13	3.0	3.0	
32 F50HAO	2 1/2-12	2 1/2-12	2 3/4	2.13	2.0	2.0	

F50F

Male Pipe Adapter
SAE-ORB / NPTF




TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2A	2 NPTF			-S	-SS	-B
4-1/8 F50F	7/16-20	1/8-27	9/16	1.00	6.0	6.0	
4-1/4 F50F	7/16-20	1/4-18	9/16	1.20	6.0	6.0	
5-1/4 F50F	1/2-20	1/4-18	5/8	1.20	6.0	6.0	
6-1/4 F50F	9/16-18	1/4-18	11/16	1.25	6.0	6.0	
6-3/8 F50F	9/16-18	3/8-18	11/16	1.34	6.0	6.0	
8-1/4 F50F	3/4-16	1/4-18	7/8	1.36	6.0	6.0	
8-3/8 F50F	3/4-16	3/8-18	7/8	1.36	6.0	6.0	
8-1/2 F50F	3/4-16	1/2-14	7/8	1.53	6.0	6.0	
10-1/2 F50F	7/8-14	1/2-14	1	1.59	6.0	6.0	
12-1/2 F50F	1 1/16-12	1/2-14	1 1/4	1.80			
12-3/4 F50F	1 1/16-12	3/4-14	1 1/4	1.80	5.0	6.0	
16-3/4 F50F	1 5/16-12	3/4-14	1 1/2	1.78			5.4
16-1 F50F	1 5/16-12	1-11 1/2	1 1/2	1.98	4.5	5.4	
20-1 1/4 F50F	1 5/8-12	1 1/4-11 1/2	1 7/8	2.02	3.0	3.6	
24-1 1/2 F50F	1 7/8-12	1 1/2-11 1/2	2 1/8	2.25			

Note: All "F50F" fittings have a 30° chamfer for sealing with NPSM swivel type fittings.

FF

Pipe Nipple
NPTF / NPTF



HPD Base # 0101


TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF			-S	-SS	-B
1/8 FF	1/8-27	1/8-27	7/16	1.06	6.0	7.2	3.9
1/4 x 1/8 FF	1/4-18	1/8-27	5/8	1.25	6.0	7.2	3.9
1/4 FF	1/4-18	1/4-18	5/8	1.45	6.0	7.2	3.9
3/8 x 1/8 FF	3/8-18	1/8-27	3/4	1.45	6.0	7.2	3.9
3/8 x 1/4 FF	3/8-18	1/4-18	3/4	1.45	6.0	7.2	3.9
3/8 FF	3/8-18	3/8-18	3/4	1.45	6.0	7.2	3.9
1/2 x 1/8 FF	1/2-14	1/8-27	7/8	1.52	7.2		
1/2 x 3/8 FF	1/2-14	3/8-18	7/8	1.70	6.0	7.2	3.9
1/2 x 1/4 FF	1/2-14	1/4-18	7/8	1.70	6.0	7.2	3.9
1/2 FF	1/2-14	1/2-14	7/8	1.89	6.0	7.2	3.9
3/4 x 1/4 FF	3/4-14	1/4-18	1 1/8	1.78	5.5	6.6	3.5
3/4 x 3/8 FF	3/4-14	3/8-18	1 1/8	1.78			
3/4 x 1/2 FF	3/4-14	1/2-14	1 1/8	1.96	5.5	6.6	3.5
3/4 FF	3/4-14	3/4-14	1 1/8	1.96	5.5	6.6	3.5
1 x 1/4 FF	1-11 1/2	1/4-18	1 3/8	1.96			
1 x 3/8 FF	1-11 1/2	3/8-18	1 3/8	1.96			
1 x 1/2 FF	1-11 1/2	1/2-14	1 3/8	2.09			
1 x 3/4 FF	1-11 1/2	3/4-14	1 3/8	2.09	4.5	5.4	
1 FF	1-11 1/2	1-11 1/2	1 3/8	2.34	4.5	5.4	3.0
1 1/4 x 1 FF	1 1/4-11 1/2	1-11 1/2	1 3/4	2.45	3.0	3.6	
1 1/4 FF	1 1/4-11 1/2	1 1/4-11 1/2	1 3/4	2.48	3.0	3.6	
1 1/2 x 1 FF	1 1/2-11 1/2	1-11 1/2	2	2.55	3.0	3.6	
1 1/2 FF	1 1/2-11 1/2	1 1/2-11 1/2	2	2.61	3.0	3.6	
2 x 1 1/2 FF	2-11 1/2	1 1/2-11 1/2	2 1/2	2.79			
2 FF	2-11 1/2	2-11 1/2	2 1/2	2.83	2.0	2.4	

Note: All steel "FF" fittings have a 30° chamfer for sealing with NPSM swivel type fittings.


Dimensions and pressures for reference only, subject to change.

FFF


Long Pipe Nipple
NPTF / NPTF





TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF			-S	-SS	-B
1/8 x 1.5 FFF	1/8-27	1/8-27	7/16	1.5	7.2	3.9	
1/8 x 2.0 FFF	1/8-27	1/8-27	7/16	2.0	7.2	3.9	
1/8 x 2.5 FFF	1/8-27	1/8-27	7/16	2.5	7.2	3.9	
1/8 x 3.0 FFF	1/8-27	1/8-27	7/16	3.0	7.2	3.9	
1/4 x 1.5 FFF	1/4-18	1/4-18	5/8	1.5	7.2	3.9	
1/4 x 2.0 FFF	1/4-18	1/4-18	5/8	2.0	7.2	3.9	
1/4 x 2.5 FFF	1/4-18	1/4-18	5/8	2.5	7.2	3.9	
1/4 x 3.0 FFF	1/4-18	1/4-18	5/8	3.0	7.2	3.9	
1/4 x 4.0 FFF	1/4-18	1/4-18	5/8	4.0	7.2	3.9	
3/8 x 2.0 FFF	3/8-18	3/8-18	3/4	2.0	7.2		
3/8 x 3.0 FFF	3/8-18	3/8-18	3/4	3.0	7.2		
3/8 x 3.5 FFF	3/8-18	3/8-18	3/4	3.5	7.2		
3/8 x 4.0 FFF	3/8-18	3/8-18	3/4	4.0	7.2		
1/2 x 2.0 FFF	1/2-14	1/2-14	7/8	2.0	7.2		
1/2 x 2.5 FFF	1/2-14	1/2-14	7/8	2.5	7.2		
1/2 x 3.0 FFF	1/2-14	1/2-14	7/8	3.0	7.2	3.9	
1/2 x 4.0 FFF	1/2-14	1/2-14	7/8	4.0	7.2		
1/2 x 6.0 FFF	1/2-14	1/2-14	7/8	6.0	7.2		
3/4 x 3.0 FFF	3/4-14	3/4-14	1 1/8	3.0	6.6		
1 x 3.0 FFF	1-11 1/2	1-11 1/2	1 3/8	3.0	5.4		

FF33MBSPT Pipe Nipple
BSPT / BSPT

TUBE FITTING PART #	END SIZE		C6 HEX (mm)	L (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPT	2 BSPT			-S	-SS	-B
1/8FF33M	1/8-28	1/8-28	10	27	6.0		
1/4x1/8FF33M	1/4-19	1/8-28	14	32	6.0		
1/4FF33M	1/4-19	1/4-19	14	37	6.0		
3/8x1/4FF33M	3/8-19	1/4-19	17	37	6.0		
3/8FF33M	3/8-19	3/8-19	17	37	6.0		
1/2FF33M	1/2-14	1/2-14	22	48	6.0		
1/2x3/8FF33M	1/2-14	3/8-19	22	43	6.0		
3/4FF33M	3/4-14	3/4-14	27	50	5.5		
3/4x1/2FF33M	3/4-14	1/2-14	27	50			
1X3/4FF33M	1-11	3/4-14	36	55	4.5		
1FF33M	1-11	1-11	36	59	4.5		

G5HG5Straight Thread Coupling
Female SAE / Female SAE

TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2B	2 UN/UNF-2B			-S	-SS	-B
4 G5HG5	7/16-20	7/16-20	11/16	1.13	7.0		
6 G5HG5	9/16-18	9/16-18	13/16	1.26	6.0		
8 G5HG5	3/4-16	3/4-16	1	1.42	5.0		
10 G5HG5	7/8-14	7/8-14	1 3/16	1.60	4.5		
12 G5HG5	1 1/16-12	1 1/16-12	1 3/8	1.85	4.5		
16 G5HG5	1 5/16-12	1 5/16-12	1 5/8	1.85	3.5		

GGPipe Coupling
NPTF / NPTFSAE 140138
HPD Base # 0202**GG44M**BSPP Female Union
BSPP / BSPP


TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	W (in.)	W1 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF					-S	-SS	-B
1/8 GG	1/8-27	1/8-27	5/8	0.75	0.63	0.63	6.0	6.0	3.9
1/4 x 1/8 GG	1/4-18	1/8-27	3/4	0.94	0.75	0.63	6.0	6.0	3.9
1/4 GG	1/4-18	1/4-18	3/4	1.13	0.75	0.75	6.0	6.0	3.9
3/8 x 1/8 GG	3/8-18	1/8-27	7/8	1.03	0.88	0.63	6.0	6.0	3.9
3/8 x 1/4 GG	3/8-18	1/4-18	7/8	1.13	0.88	0.75	6.0	6.0	3.9
3/8 GG	3/8-18	3/8-18	7/8	1.13	0.88	0.88	6.0	6.0	3.9
1/2 x 1/8 GG	1/2-14	1/8-27	1 1/8	1.06	1.13	0.63		6.0	
1/2 x 1/4 GG	1/2-14	1/4-18	1 1/8	1.38	1.13	0.75	5.0	6.0	3.2
1/2 x 3/8 GG	1/2-14	3/8-18	1 1/8	1.50	1.13	0.88	5.0	6.0	3.2
1/2 GG	1/2-14	1/2-14	1 1/8	1.50	1.13	1.13	5.0	6.0	3.2
3/4 x 1/4 GG	3/4-14	1/4-18	1 3/8	1.55	1.36	0.75		4.8	
3/4 x 1/2 GG	3/4-14	1/2-14	1 3/8	1.88	1.36	1.13	4.0	4.8	
3/4 GG	3/4-14	3/4-14	1 3/8	1.53	1.38	1.38	4.0	4.8	2.6
1 GG	1-11 1/2	1-11 1/2	1 5/8	1.89	1.63	1.63	3.0	3.6	1.9
1 x 1/2 GG	1-11 1/2	1/2-14	1 5/8	1.77	1.63	1.13		3.6	
1 x 3/4 GG	1-11 1/2	3/4-14	1 5/8	1.77	1.63	1.38		3.6	
1 1/4 GG	1 1/4-11 1/2	1 1/4-11 1/2	2	1.93	2.00	2.00	2.5	3.0	
1 1/4 x 1 GG	1 1/4-11 1/2	1-11 1/2	2	1.93	2.00	1.63		3.0	
1 1/2 GG	1 1/2-11 1/2	1 1/2-11 1/2	2 3/8	1.93	2.38	2.38	2.0	2.4	
1 1/2 x 1 1/4 GG	1 1/2-11 1/2	1 1/4-11 1/2	2 3/8	1.93	2.37	2.37		2.4	
2 GG	2-11 1/2	2-11 1/2	2 7/8	1.97	2.88	2.88		2.4	

TUBE FITTING PART #	END SIZE		C6 HEX (mm)	L (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPP	2 BSPP			-S	-SS	-B
1/8GG44M	1/8-28	1/8-28	14	19	6.0		
1/4X1/8GG44M	1/4-19	1/8-28	17	24	6.0		
1/4GG44M	1/4-19	1/4-19	17	28	6.0		
3/8GG44M	3/8-19	3/8-19	22	28	6.0		
3/8x1/4GG44M	3/8-19	1/4-19	22	28	6.0		
1/2x3/8GG44M	1/2-14	3/8-19	27	31	5.0		
1/2GG44M	1/2-14	1/2-14	27	32.5	5.0		
1GG44M	1-11	1-11	46	42	3.0		

Dimensions and pressures for reference only, subject to change.

FHG4


Conversion Adapter
NPTF / BSPP



TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 BSPP			-S	-SS	-B
1/4X1/4FHG4	1/4-18	1/4-19	3/4	1.33	6.0		
1/4X3/8FHG4	1/4-18	3/8-19	13/16	1.40	6.0		
3/8X1/4FHG4	3/8-18	1/4-19	3/4	1.31	6.0		
3/8X3/8FHG4	3/8-18	3/8-19	1	1.34	6.0		
1/2X3/8FHG4	1/2-14	3/8-19	15/16	1.50	6.0		
1/2X1/2FHG4	1/2-14	1/2-14	1 1/8	1.66	5.0		
3/4X3/4FHG4	3/4-14	3/4-14	1 7/16	1.75	4.0		

F87OHG87


Reducer / Expander
ISO 6149 / ISO 6149



TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 METRIC STR	2 METRIC STR			-S	-SS	-B
M8M10F87OHG87M	M8X1	M10X1	17	27.0	10.0		
M10M8F87OHG87M	M10X1	M8X1	14	27.5	10.0		
M10M12F87OHG87M	M10X1	M12X1.5	19	30.0	8.0		
M12M10F87OHG87M	M12X1.5	M10X1	17	29.5	10.0		
M12M12F87OHG87M	M12X1.5	M14X1.5	22	32.0	7.0		
M12M16F87OHG87M	M12X1.5	M16X1.5	24	33.5	6.0		
M14M12F87OHG87M	M14X1.5	M12X1.5	19	32.0	8.0		
M14M16F87OHG87M	M14X1.5	M16X1.5	24	33.5	6.0		
M16M14F87OHG87M	M16X1.5	M14X1.5	22	34.0	7.0		
M16M18F87OHG87M	M16X1.5	M18X1.5	27	37.0	6.0		
M18M16F87OHG87M	M18X1.5	M16X1.5	24	37.0	6.0		
M18M20F87OHG87M	M18X1.5	M20X1.5	30	39.5	6.0		
M20M18F87OHG87M	M20X1.5	M18X1.5	27	38.5	6.0		
M20M22F87OHG87M	M20X1.5	M22X1.5	30	39.5	5.0		
M22M20F87OHG87M	M22X1.5	M20X1.5	27	41.5	5.0		
M27M22F87OHG87M	M27X2.0	M22X1.5	32	46.0	5.0		
M27M33F87OHG87M	M27X2.0	M33X2.0	46	52.0	5.0		
M33M27F87OHG87M	M33X2.0	M27X2.0	41	48	5.0		
M33M42F87OHG87M	M33X2.0	M42X2.0	55	54.0	4.0		
M42M27F87OHG87M	M42X2.0	M27X2.0	50	54.0	4.0		
M42M33F87OHG87M	M42X2.0	M33X2.0	50	54.0	3.0		
M42M48F87OHG87M	M42X2.0	M48X2.0	65	57.0			

F8OHG5


Conversion Adapter
Metric-ORR / SAE-ORB
(for ISO 9974 / DIN 3852-1 Port)



TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L1 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 METRIC STR	2 UN/UNF-2B			-S	-SS	-B
M10-4F8OHG5	M10x1	7/16-20	11/16	1.06	5.0		
M10-6F8OHG5	M10X1	9/16-18	7/8	1.15	5.0		
M14-6F8OHG5	M14x1.5	9/16-18	13/16	1.19	5.0		
M16-8F8OHG5	M16x1.5	3/4-16	1	1.31	5.0		
M18-8F8OHG5	M18X1.5	3/4-16	1	1.38	3.5		
M22-10F8OHG5	M22x1.5	7/8-14	1 1/8	1.5	3.5		
M27-12F8OHG5	M27x2	1 1/16-12	1 1/4	1.88	3.5		
M33-16F8OHG5	M33x2	1 5/16-12	1 5/8	1.91			
M42-20F8OHG5	M42x2	1 5/8-12	2	1.91			

F8OHG

Conversion Adapter
Metric-ORR / NPTF
(for ISO 9974 / DIN 3852-1 Port)




TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 METRIC STR	2 NPTF			-S	-SS	-B
M10-1/8F8OHG	M10X1.0	1/8-27	9/16	0.99	5.0		
M12-1/4F8OHG	M12X1.5	1/4-18	3/4	1.24	5.0		
M14-1/4F8OHG	M14X1.5	1/4-18	3/4	1.24	5.0		
M16-3/8F8OHG	M16X1.5	3/8-18	7/8	1.36	5.0		
M16-1/2F8OHG	M16X1.5	1/2-14	1 1/8	1.58	5.0		
M18-3/8F8OHG	M18X1.5	3/8-18	15/16	1.42	5.0		
M18-1/2F8OHG	M18X1.5	1/2-14	1 1/8	1.67	5.0		
M22-1/2F8OHG	M22X1.5	1/2-14	1 1/8	1.68	3.5		
M27-3/4F8OHG	M27X2.0	3/4-14	1 3/8	1.87	3.5		
M33-1F8OHG	M33X2.0	1-11 1/2	1 5/8	2.11	3.0		


Dimensions and pressures for reference only, subject to change.

F4OHG5

Conversion Adapter
BSPP-ORR / SAE-ORB
(for ISO 1179-1 / DIN 3852-2 Port)

**F4OHG**

Conversion Adapter
BSPP-ORR / NPTF
(for ISO 1179-1 / DIN 3852-2 Port)




TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPP	2 UN/UNF-2B			-S	-SS	-B
1/8-4F4OHG5	1/8-28	7/16-20	11/16	1	5.0		
1/4-4F4OHG5	1/4-19	7/16-20	3/4	1.11	5.0		
1/4-6F4OHG5	1/4-19	9/16-18	13/16	1.25	5.0		
3/8-4F4OHG5	3/8-19	7/16-20	7/8	1.19	5.0		
3/8-5F4OHG5	3/8-19	1/2-20	7/8	1.19	5.0		
3/8-6F4OHG5	3/8-19	9/16-18	7/8	1.25	5.0	5.0	
3/8-8F4OHG5	3/8-19	3/4-16	1	1.33	5.0		
1/2-10F4OHG5	1/2-14	7/8-14	1 1/8	1.6	3.5		
3/4-12F4OHG5	3/4-14	1 1/16-12	1 3/8	1.74	3.5	3.5	
1-16F4OHG5	1-11	1 5/16-12	1 3/4	1.92	3.5		
1 1/4-16F4OHG5	1 1/4-11	1 5/16-12	2	1.95	2.0		
1 1/4-20F4OHG5	1 1/4-11	1 5/8-12	2	1.95	2.0		

TUBE FITTING PART #	END SIZE		C6 HEX (in.)	L (in)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPP	2 NPTF			-S	-SS	-B
1/8x1/8F4OHG	1/8-28	1/8-27	5/8	0.97	5		
1/4x1/4F4OHG	1/4-19	1/4-18	3/4	1.28	5		
3/8x3/8F4OHG	3/8-19	3/8-18	7/8	1.33	5		
1/2x1/2F4OHG	1/2-14	1/2-14	1 1/8	1.73	3.5		
3/4x3/4F4OHG	3/4-14	3/4-14	1 3/8	1.77	3.5		
1x1F4OHG	1-11	1-11 1/2	1 5/8	2.17	3		

PTR34

BSPT Reducing Adapter
BSPT / BSPP




TUBE FITTING PART #	END SIZE		C HEX (in.)	L2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPT	2 BSPP			-S	-SS	-B
1/4X1/8PTR34M	1/4-19	1/8-28	17	28	6.0		
3/8X1/4PTR34M	3/8-19	1/4-19	19	33	6.0		
1/2X1/4PTR34M	1/2-14	1/4-19	22	39	5.0		
1/2X3/8PTR34M	1/2-14	3/8-19	22	39	5.0		

Dimensions and pressures for reference only, subject to change.

RI-ED

BSPP Reducing Adapter / Expander
BSPP / BSPP-ED
(for ISO 1179-1 / DIN 3852-2 Port)




TUBE FITTING PART #	END SIZE		d3 (mm)	L (mm)	S1 (mm)	Fig.	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPP	2 BSPP					CF	71	MS
RI1/8EDX1/4	G1/8A	G1/4	14	31	19	B	5.8	5.8	
RI1/8EDX3/8	G1/8A	G3/8	14	32	24	B	5.8	5.8	
RI1/4EDX1/8	G1/4A	G1/8	19	29	19	B	5.8	5.8	
RI1/4EDX3/8	G1/4A	G3/8	19	36	24	B	5.8	5.8	
RI1/4EDX1/2	G1/4A	G1/2	19	40	30	B	5.8	5.8	
RI1/4EDX3/4	G1/4A	G3/4	19	43	36	B	5.8		
RI3/8EDX1/8	G3/8A	G1/8	22	22.5	22	A	5.8		
RI3/8EDX1/4	G3/8A	G1/4	22	36	22	B	5.8	5.8	
RI3/8EDX1/2	G3/8A	G1/2	22	41	30	B	5.8		
RI3/8EDX3/4	G3/8A	G3/4	22	44	36	B	4.5		
RI1/2EDX1/8	G1/2A	G1/8	27	24	27	A	5.8	5.8	
RI1/2EDX1/4	G1/2A	G1/4	27	24	27	A	5.8	5.8	
RI1/2EDX3/8	G1/2A	G3/4	27	46	36	B	4.5		
RI1/2EDX1	G1/2A	G1	27	49	41	B	4.5		
RI1/2EDX11/4	G1/2A	G1 1/4	27	53	55	B	4.5		
RI3/4EDX1/4	G3/4A	G1/4	32	26	32	A	4.5	4.5	
RI3/4EDX3/8	G3/4A	G3/8	32	26	32	A	4.5	4.5	
RI3/4EDX1/2	G3/4A	G1/2	32	43	32	B	4.5	4.5	
RI3/4EDX1	G3/4A	G1	32	51	41	B	4.5		
RI3/4EDX11/4	G3/4A	G1 1/4	32	55	55	B	4.5		
RI3/4EDX11/2	G3/4A	G1 1/2	32	57	60	B			
RI1EDX1/4	G1A	G1/4	40	29	41	A	4.5	4.5	
RI1EDX3/8	G1A	G3/8	40	29	41	A	4.5	4.5	
RI1EDX1/2	G1A	G1/2	40	29	41	A	4.5	4.5	
RI1EDX3/4	G1A	G3/4	40	49	41	B	4.5	4.5	
RI1EDX11/4	G1A	G1 1/4	40	57	55	B	4.5	4.5	
RI1EDX11/2	G1A	G1 1/2	40	59	60	B	3.6	3.6	
RI11/4EDX1/2	G1 1/4A	G1/2	50	32	50	A	4.5		
RI11/4EDX3/4	G1 1/4A	G3/4	50	32	50	A	4.5	4.5	
RI11/4EDX1	G1 1/4A	G1	50	53	50	B	4.5	4.5	
RI11/4EDX11/2	G1 1/4A	G1 1/2	50	60	60	B	3.6		
RI11/2EDX1/2	G1 1/2A	G1/2	55	36	55	A	3.6		
RI11/2EDX3/4	G1 1/2A	G3/4	55	36	55	A	3.6	3.6	
RI11/2EDX1	G1 1/2A	G1	55	36	55	A	3.6	3.6	
RI11/2EDX11/4	G1 1/2A	G1 1/4	55	58	55	B	3.6		
RI2EDX11/2	G2 A	G1 1/2	72	65	70	B	2.3		

Dimensions and pressures for reference only, subject to change.

RI

BSPP Reducing Adapter / Expander
BSPP / BSPP-CF
(for ISO 1179-1 / DIN 3852-2 Port)




TUBE FITTING PART #	END SIZE		d3 (mm)	L (mm)	S1 (mm)	Fig.	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 BSPP	2 BSPP					CFX	71X	MSX
RI1/8X1/4	G 1/8A	G 1/4	14	31	19	B	5.8		
RI1/8X3/8	G 1/8A	G 3/8	14	32	24	B	5.8		
RI1/4X1/8	G 1/4A	G 1/8	18	28	19	B	5.8		
RI1/4X3/8	G 1/4A	G 3/8	18	36	24	B	5.8	5.8	
RI1/4X1/2	G 1/4A	G 1/2	18	40	30	B	5.8	5.8	
RI1/4X3/4	G 1/4A	G 3/4	18	43	36	B	4.5		
RI3/8X1/8	G 3/8A	G 1/8	22	22.5	22	A	5.8		
RI3/8X1/4	G 3/8A	G 1/4	22	36	22	B	5.8	5.8	
RI3/8X1/2	G 3/8A	G 1/2	22	41	30	B	5.8		
RI3/8X3/4	G 3/8A	G 3/4	22	44	36	B			
RI1/2X1/8	G 1/2A	G 1/8	26	24	27	A	5.8		
RI1/2X1/4	G 1/2A	G 1/4	26	24	27	A	4.5	4.5	
RI1/2X3/8	G 1/2A	G 3/8	26	36	27	B	4.5	4.5	3.0
RI1/2X3/4	G 1/2A	G 3/4	26	46	36	B	4.5	4.5	3.0
RI1/2X1	G 1/2A	G 1	26	49	41	B	2.3		
RI1/2X11/4	G 1/2A	G 1 1/4	26	53	55	B	4.5		
RI3/4X1/4	G 3/4A	G 1/4	32	26	32	A	4.5		
RI3/4X3/8	G 3/4A	G 3/8	32	26	32	A	4.5	4.5	
RI3/4X1/2	G 3/4A	G 1/2	32	41	32	B	4.5	4.5	
RI3/4X1	G 3/4A	G 1	32	51	41	B	2.3		1.5
RI3/4X11/4	G 3/4A	G 1 1/4	32	55	55	B	2.3		
RI3/4X11/2	G 3/4A	G 1 1/2	32	57	60	B	4.5		
RI1X1/4	G 1A	G 1/4	39	29	41	A	4.5	4.5	
RI1X3/8	G 1A	G 3/8	39	29	41	A	4.5		
RI1X1/2	G 1A	G 1/2	39	29	41	A	4.5		
RI1X3/4	G 1A	G 3/4	39	47	41	B	2.3	2.3	
RI1X11/4	G 1A	G 1 1/4	39	57	55	B	2.3	2.3	
RI1X11/2	G 1A	G 1 1/2	39	59	60	B	2.3		
RI11/4X1/2	G 1 1/4A	G 1/2	49	32	50	A	2.3		
RI11/4X3/4	G 1 1/4A	G 3/4	49	32	50	A	2.3		
RI11/4X1	G 1 1/4A	G 1	49	52	50	B	2.3	2.3	
RI11/4X11/2	G 1 1/4A	G 1 1/2	49	60	60	B	2.3		
RI11/2X1/2	G 1 1/2A	G 1/2	55	36	55	A	2.3		
RI11/2X3/4	G 1 1/2A	G 3/4	55	36	55	A	2.3		
RI11/2X1	G 1 1/2A	G 1	55	36	55	A	2.3		
RI11/2X11/4	G 1 1/2A	G 1 1/4	55	58	55	B	2.3		
RI2X11/2	G 2A	G 1 1/2	68	62	70	B			

Dimensions and pressures for reference only, subject to change.

AOE4G


Extra Long Female Pipe Elbow
NPTF / SAE-ORB

HPD Base # 5502

**CR**

Male Pipe Elbow
NPTF / NPTF

SAE 140237*



* Y – Across
Wrench Flats

TUBE FITTING PART #	END SIZE		M1 (in.)	N (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2A	2 NPTF				-S	-SS	-B
8-3/8 AOE4G	3/4-16	3/8-18	2.94	0.63	7/8	4.5		
10-1/2 AOE4G	7/8-14	1/2-14	3.56	0.75	1 1/16	3.0		
12-3/4 AOE4G	1 1/16-12	3/4-14	4.06	0.81	1 5/16	3.0		
16-1 AOE4G	1 5/16-12	1-11 1/2	4.63	1.00	1 5/8	1.8		


TUBE FITTING PART #	END SIZE		N (in.)	N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF				-S	-SS	-B
1/8 CR	1/8-27	1/8-27	0.78	0.78	7/16	6.0	6.0	3.9
1/4 CR	1/4-18	1/4-18	1.09	1.09	9/16	6.0	6.0	3.9
3/8 CR	3/8-18	3/8-18	1.22	1.22	3/4	6.0	6.0	3.9
3/8 x 1/4 CR	3/8-18	1/4-18	1.22	1.22	3/4	6.0	6.0	
1/2 CR	1/2-14	1/2-14	1.47	1.47	7/8	6.0	6.0	3.9
1/2 x 3/8 CR	1/2-14	3/8-18	1.47	1.28	7/8	6.0	6.0	
3/4 CR	3/4-14	3/4-14	1.59	1.59	1 1/16	4.0	4.0	2.6
3/4 x 1/2 CR	3/4-14	1/2-14	1.59	1.47	1 1/16	4.0		
1 CR	1-11 1/2	1-11 1/2	1.97	1.97	1 5/8		3.0	
1 x 3/4 CR	1-11 1/2	3/4-14	1.97	1.78	1 5/16	3.0		
1 1/4 CR	1 1/4-11 1/2	1 1/4-11 1/2	2.22	2.22	1 7/8	2.5	2.5	
1 1/2 CR	1 1/2-11 1/2	1 1/2-11 1/2	2.34	2.34	1 7/8	2.5		

* Not shown in SAE J514, but coded per SAE J846.

CD


Street Elbow
NPTF / NPTF

SAE 140239
HPD Base # 2102

**DD**

Female Pipe Elbow
NPTF / NPTF

SAE 140238
HPD Base # 2202




TUBE FITTING PART #	END SIZE		N (in.)	N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF				-S	-SS	-B
1/8 CD	1/8-27	1/8-27	0.78	0.66	9/16	5.0	5.0	3.2
1/8 x 1/4 CD	1/8-27	1/4-18	0.90	0.88	9/16	5.0	5.0	
1/4 CD	1/4-18	1/4-18	1.09	0.88	3/4	5.0	5.0	3.2
1/4 x 1/8 CD	1/4-18	1/8-27	1.09	0.66	9/16	5.0	5.0	
1/4 x 1/2 CD	1/4-18	1/2-14	1.28	1.23	1 1/16	3.0		
1/4 x 3/8 CD	1/4-18	3/8-18	1.22	1.01	7/8	4.5	4.5	
3/8 CD	3/8-18	3/8-18	1.22	1.02	7/8	4.5	4.5	3.0
3/8 x 1/4 CD	3/8-18	1/4-18	1.22	0.88	3/4	5.0	5.0	
3/8 x 1/2 CD	3/8-18	1/2-14	1.28	1.23	1 1/16	3.0	3.0	
1/2 CD	1/2-14	1/2-14	1.47	1.23	1 1/16	3.0	3.0	1.9
1/2 x 3/8 CD	1/2-14	3/8-18	1.48	1.25	7/8	4.5	4.5	
1/2 x 3/4 CD	1/2-14	3/4-14	1.58	1.36	1 5/16	3.0		
3/4 CD	3/4-14	3/4-14	1.59	1.36	1 5/16	3.0	3.0	1.9
3/4 x 1/2 CD	3/4-14	1/2-14	1.59	1.23	1 1/16	3.0	3.0	
1 CD	1-11 1/2	1-11 1/2	1.97	1.63	1 5/8	1.8	1.8	1.2
1 1/4 CD	1 1/4-11 1/2	1 1/4-11 1/2	2.38	1.70	1 7/8	1.5	1.5	
1 1/4 x 1 1/2 CD	1 1/4-11 1/2	1 1/2-11 1/2	2.61	2.08	2 1/2	1.5		
1 1/2 CD	1 1/2-11 1/2	1 1/2-11 1/2	2.64	2.08	2 1/2	1.5	1.5	

TUBE FITTING PART #	END SIZE		N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	2 NPTF			-S	-SS	-B
1/8 DD	1/8-27	1/8-27	0.66	9/16	5.0	5.0	3.2
1/4 DD	1/4-18	1/4-18	0.88	3/4	5.0	5.0	3.2
3/8 DD	3/8-18	3/8-18	1.02	7/8	4.5	4.5	3.0
1/2 DD	1/2-14	1/2-14	1.23	1 1/16	3.0	3.0	1.9
1/2 x 3/8 DD	1/2-14	3/8-18	1.23	1 1/16			
3/4 DD	3/4-14	3/4-14	1.36	1 5/8	3.0	3.0	1.9
1 DD	1-11 1/2	1-11 1/2	1.63	1 7/8	1.8	1.8	1.2
1 1/4 DD	1 1/4-11 1/2	1 1/4-11 1/2	1.70	1 7/8	1.5	1.5	
1 1/2 DD	1 1/2-11 1/2	1 1/2-11 1/2	2.08	2 1/2	1.5	1.5	

Dimensions and pressures for reference only, subject to change.

A87LPOEG87LPM

ISO 6149* Female Elbow
SHORT ISO 6149 / SHORT ISO 6149




TUBE FITTING PART #	END SIZE		I (mm)	L1 (mm)	L2 (mm)	S1 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 Metric	2 Metric					-S	-SS	-B
M08A87LPOEG87LPM	M8X1	M8X1	8.5	13.5	7.5	15			
M10A87LPOEG87LPM	M10X1	M10X1	8.5	14.5	7.5	15			
M12A87LPOEG87LPM	M12X1.5	M12X1.5	11	17	10	20	3.6		
M14A87LPOEG87LPM	M14X1.5	M14X1.5	11	18	10	20	3.6		

* Male and female thread lengths have been shortened for compact design. The lengths do not conform to ISO 6149.

A4OEG4M

BSPP Female Elbow
BSPP-ORR / BSPP




TUBE FITTING PART #	END SIZE		D1 (mm)	I (mm)	L1 (mm)	L2 (mm)	S1 (mm)	STANDARD MATERIAL FROM STOCK		
	1 BSPP	2 BSPP						-S	-SS	-B
2-2A4OEG4M	G 1/8 A	G 1/8 A	15	6.5	18.5	7	15	3.6		

* Male and female thread lengths have been shortened for compact design. The lengths do not conform to ISO 1179 / DIN 3852-2.

G5G5JAO

Straight Thread Branch Tee
SAE-ORB (all three ends)




* Y - Across
Wrench Flats

TUBE FITTING PART #	END SIZE			M (in.)	N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2B	2 UN/UNF-2B	3 UN/UNF-2A				-S	-SS	-B
4 G5G5JAO	7/16-20	7/16-20	7/16-20	1.23	0.63	3/4	5.0		
6 G5G5JAO	9/16-18	9/16-18	9/16-18	1.38	0.75	7/8	5.0		
8 G5G5JAO	3/4-16	3/4-16	3/4-16	1.59	0.88	1 1/16	5.0		
10 G5G5JAO	7/8-14	7/8-14	7/8-14	1.81	1.02	1 1/16	4.5		
12 G5G5JAO	1 1/16-12	1 1/16-12	1 1/16-12	2.00	1.21	1 5/16	3.0		
16 G5G5JAO	1 5/16-12	1 5/16-12	1 5/16-12	2.25	1.33	1 5/8	3.0		

Dimensions and pressures for reference only, subject to change.

AOG5JG5

Straight Thread Run Tee
SAE-ORB (all three ends)




* Y – Across Wrench Flats

TUBE FITTING PART #	END SIZE			M (in.)	N2 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2A	2 UN/UNF-2B	3 UN/UNF-2B				-S	-SS	-B
4 AOG5JG5	7/16-20	7/16-20	7/16-20	1.23	0.74	3/4	5.0		
6 AOG5JG5	9/16-18	9/16-18	9/16-18	1.38	0.86	7/8	5.0		
8 AOG5JG5	3/4-16	3/4-16	3/4-16	1.59	1.03	1 1/16	5.0		
10 AOG5JG5	7/8-14	7/8-14	7/8-14	1.81	1.18	1 1/16	4.5		
12 AOG5JG5	1 1/16-12	1 1/16-12	1 1/16-12	2.00	1.39	1 5/16	3.0		
16 AOG5JG5	1 5/16-12	1 5/16-12	1 5/16-12	2.25	1.52	1 5/8	3.0		

G5G5JG5


Female Straight Thread Tee
SAE-ORB (all three ends)



* Y – Across
Wrench Flats

RRS

Male Pipe Tee
NPTF (all three ends)




SAE 140437

TUBE FITTING PART #	END SIZE		N2 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1-3 UN/UNF-2B	-S	-SS	-B			
4 G5G5JG5	7/16-20	0.74	3/4	5.0			
6 G5G5JG5	9/16-18	0.86	3/4	5.0			
8 G5G5JG5	3/4-16	1.03	1 1/16	5.0			
10 G5G5JG5	7/8-14	1.18	1 1/16	4.5			
12 G5G5JG5	1 1/16-12	1.39	1 5/16	3.0			
16 G5G5JG5	1 5/16-12	1.52	1 5/8	3.0			

TUBE FITTING PART #	END SIZE		N (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1-3 NPTF	-S	-SS	-B			
1/8 RRS	1/8-27	0.78	7/16	6.0	6.0	3.9	
1/4 RRS	1/4-18	1.09	9/16	6.0	6.0	3.9	
3/8 RRS	3/8-18	1.22	3/4	6.0	6.0	3.9	
1/2 RRS	1/2-14	1.47	7/8	6.0	6.0	3.9	
3/4 RRS	3/4-14	1.59	1 1/16	4.0	4.0	3.9	

MMS


Male Branch Tee
NPTF (all three ends)



SAE 140425
HPD Base # 212T

MRO

Male Run Tee
NPTF (all three ends)



SAE 140424
HPD Base # 012T

TUBE FITTING PART #	END SIZE		N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1-3 NPTF	N (in.)			-S	-SS	-B
1/8 MMS	1/8-27	0.78	0.66	9/16	5.0	5.0	3.2
1/4 MMS	1/4-18	1.09	0.88	3/4	5.0	5.0	3.2
3/8 MMS	3/8-18	1.22	1.02	7/8	4.5	4.5	3.0
1/2 MMS	1/2-14	1.47	1.23	1 1/16	3.0	3.0	1.9
3/4 MMS	3/4-14	1.59	1.36	1 5/16	3.0	3.0	3.0
1 MMS	1-11 1/2	1.97	1.62	1 5/8	1.8	1.8	1.8


TUBE FITTING PART #	END SIZE		N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1-3 NPTF	N (in.)			-S	-SS	-B
1/8 MRO	1/8-27	0.78	0.66	9/16	5.0	5.0	3.2
1/4 MRO	1/4-18	1.09	0.88	3/4	5.0	5.0	3.2
3/8 MRO	3/8-18	1.22	1.02	7/8	4.5	4.5	3.0
1/2 MRO	1/2-14	1.47	1.23	1 1/16	3.0	3.0	1.9
3/4 MRO	3/4-14	1.59	1.36	1 5/16	3.0	3.0	3.0
1 MRO	1-11 1/2	1.97	1.63	1 5/8	1.8	1.8	1.8
1 1/4 MRO	1 1/4-11 1/2	2.38	1.70	1 7/8	1.5	1.5	
1 1/2 MRO	1 1/2-11 1/2	2.64	2.08	2 1/2	1.5	1.5	

Dimensions and pressures for reference only, subject to change.


MMO

Female Pipe Tee
NPTF (all three ends)

SAE 140438
HPD Base # 022T

**MMO444**

Female BSPP Tee
BSPP (all three ends)




TUBE FITTING PART #	END SIZE 1-3 NPTF	N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
				-S	-SS	-B
1/8 MMO	1/8-27	0.66	9/16	5.0	5.0	3.2
1/4 MMO	1/4-18	0.88	3/4	5.0	5.0	3.2
3/8 MMO	3/8-18	1.02	7/8	4.5	4.5	3.0
1/2 MMO	1/2-14	1.23	1 1/16	3.0	3.0	1.9
3/4 MMO	3/4-14	1.36	1 5/16	3.0	3.0	1.9
1 MMO	1-11 1/2	1.63	1 5/8	1.8	1.8	1.2
1 1/4 MMO	1 1/4-11 1/2	1.70	1 7/8	1.5	1.5	
1 1/2 MMO	1 1/2-11 1/2	2.08	2 1/2	1.5	1.5	

KMMOO


Female Pipe Cross
NPTF (all four ends)

SAE 140538
HPD Base # 022X

**P5ON**

Hex Head Plug
SAE-ORB

SAE 090109A
HPD Base # 05CP



TUBE FITTING PART #	END SIZE 1-4 NPTF	N1 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
				-S	-SS	-B
1/8 KMMOO	1/8-27	0.66	9/16	5.0	5.0	3.2
1/4 KMMOO	1/4-18	0.88	3/4	5.0	5.0	3.2
3/8 KMMOO	3/8-18	1.02	7/8	4.5	4.5	
1/2 KMMOO	1/2-14	1.23	1 1/16	3.0	3.0	1.9
3/4 KMMOO	3/4-14	1.36	1 5/16	3.0		
1 KMMOO	1-11 1/2	1.63	1 5/8	1.8		


TUBE FITTING PART #	END SIZE 1 UN/UNF-2A	C4 HEX (in.)	I1 (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
					-S	-SS	-B
2 P5ON	5/16-24	7/16	0.30	0.60	7.5	9.0	
3 P5ON	3/8-24	1/2	0.30	0.60	7.5	9.0	
4 P5ON	7/16-20	9/16	0.36	0.67	7.5	9.0	
5 P5ON	1/2-20	5/8	0.36	0.67	6.0	7.2	
6 P5ON	9/16-18	11/16	0.39	0.73	6.0	7.2	
8 P5ON	3/4-16	7/8	0.44	0.80	6.0	7.2	
10 P5ON	7/8-14	1	0.50	0.94	6.0	7.2	
12 P5ON	1 1/16-12	1 1/4	0.59	1.09	6.0	7.2	
14 P5ON	1 3/16-12	1 3/8	0.59	1.09	5.5		
16 P5ON	1 5/16-12	1 1/2	0.59	1.13	5.5	6.6	
20 P5ON	1 5/8-12	1 7/8	0.59	1.20	4.0	4.8	
24 P5ON	1 7/8-12	2 1/8	0.59	1.27	3.0	3.6	
32 P5ON	2 1/2-12	2 3/4	0.59	1.44	2.0	2.4	

Dimensions and pressures for reference only, subject to change.

HP5ON


Hollow Hex Plug
SAE-ORB

SAE 090109B
HPD Base # 05HP

**HP**

Hex Head Pipe Plug
NPTF


SAE 130109E
HPD Base # 01CP



TUBE FITTING PART #	END SIZE		C5 HEX (in.)	I1 (in.)	L1 (in.)	X DIA (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 UN/UNF-2A	-S					-S	-SS	-B
2 HP5ON	5/16-24	1/8	0.30	0.40	0.44	6.0	6.0		
3 HP5ON	3/8-24	1/8	0.30	0.40	0.50	6.0	6.0		
4 HP5ON	7/16-20	3/16	0.36	0.47	0.56	6.0	6.0		
5 HP5ON	1/2-20	3/16	0.36	0.47	0.63	6.0	6.0		
6 HP5ON	9/16-18	1/4	0.40	0.50	0.69	6.0	6.0		
8 HP5ON	3/4-16	5/16	0.44	0.58	0.88	6.0	6.0		
10 HP5ON	7/8-14	3/8	0.50	0.65	1.00	6.0	6.0		
12 HP5ON	1 1/16-12	9/16	0.59	0.77	1.25	6.0	6.0		
14 HP5ON	1 3/16-12	9/16	0.59	0.77	1.38	5.5			
16 HP5ON	1 5/16-12	5/8	0.59	0.77	1.50	5.5	5.5		
20 HP5ON	1 5/8-12	3/4	0.59	0.77	1.88	4.0			
24 HP5ON	1 7/8-12	3/4	0.59	0.77	2.13	3.0	3.0		


SHP

Square Head Plug
NPTF

**HHP**

Hollow Hex Pipe Plug
NPTF

SAE 130109N
HPD Base # 01HP




TUBE FITTING PART #	END SIZE		C SQUARE (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	-S			-S	-SS	-B
1/8 SHP	1/8-27	9/32	0.51	6.0	7.2		
1/4 SHP	1/4-18	3/8	0.75	6.0			
3/8 SHP	3/8-18	7/16	0.83	6.0			
1/2 SHP	1/2-14	9/16	1.08	6.0			
3/4 SHP	3/4-14	5/8	1.14	6.0			
1 SHP	1-11 1/2	13/16	1.38	5.5			

TUBE FITTING PART #	END SIZE		C5 INTERNAL HEX (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF	B (in.)		-S	-SS	-B
1/16 HHP	1/16-27	0.30	5/32	6.0		
1/8 HHP	1/8-27	0.30	3/16	6.0	7.2	3.9
1/4 HHP	1/4-18	0.46	1/4	6.0	7.2	3.9
3/8 HHP	3/8-18	0.46	5/16	6.0	7.2	
1/2 HHP	1/2-14	0.61	3/8	6.0	7.2	
3/4 HHP	3/4-14	0.62	9/16	5.5	6.6	
1 HHP	1-11 1/2	0.77	3/4	4.5	5.4	
1 1/4 HHP	1 1/4-11 1/2	0.77	3/4	3.0		
1 1/2 HHP	1 1/2-11 1/2	0.83	3/4	3.0		
2 HHP	2-11 1/2	0.86	3/4	2.0		


Dimensions and pressures for reference only, subject to change.

HPC

Hex Pipe Cap
NPTF

**P87OMN**

ISO 6149 Hex Head Plug
ISO 6149
(for ISO 6149-1 Port)



SAE J2244-4* 62M0109A

TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 NPTF				-S	-SS	-B
1/8 HPC	1/8-27	9/16	.75		6.0		
1/4 HPC	1/4-18	3/4	.91		6.0		
3/8 HPC	3/8-18	7/8	1.03		6.0		
1/2 HPC	1/2-14	1 1/16	1.34		6.0		
3/4 HPC	3/4-14	1 1/4	1.44		4.8		
1 HPC	1-11 1/2	1 5/8	1.68		3.6		
1 1/2 HPC	1 1/2-1 1/2	2 3/8	1.92		2.4		


TUBE FITTING PART #	END SIZE		L4 (mm)	L11 (mm)	S HEX (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 THREAD					-S	-SS	-B
M8P87OMN	M8X1		8.5	16.2	12			
M10P87OMN	M10X1		8.5	16.2	14	8.0		
M12P87OMN	M12X1.5		11	18.5	17	9.0		
M14P87OMN	M14X1.5		11	19.5	19	9.0		
M16P87OMN	M16X1.5		11.5	21.5	22	9.0		
M18P87OMN	M18X1.5		12.5	23.5	24	9.0		
M20P87OMN	M20X1.5		12.5	24	27			
M22P87OMN	M22X1.5		13	25.5	27	6.0		
M27P87OMN	M27X2		16	32	32	6.0		
M30P87OMN	M30X2		16	32	36			
M33P87OMN	M33X2		16	32	41	6.0		
M42P87OMN	M42X2		16	34	50	4.0		
M48P87OMN	M48X2		17.5	35.5	55			
M60P87OMN	M60X2		17.5	33	65			

* SAE J2244-4 and ISO 6149-4 are draft standards.


VSTI M-OR

ISO 6149 Hollow Hex Plug
ISO 6149
(for ISO 6149-1 Port)

SAE J2244-4* 62M0109B

**VSTI M-ED**

Metric Hollow Hex Plug
Metric-ED
(for ISO 9974-1 / DIN 3852-1 Port)



TUBE FITTING PART #	END SIZE		D (mm)	L (mm)	S6 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 THREAD					CF*	71*	MS*
VSTI10X1OR	M10 x 1	13	13.5	5	9.1			
VSTI12X1.5OR	M12 x 1.5	17	15.1	6	9.1			
VSTI14X1.5OR	M14 x 1.5	19	16	6	9.1			
VSTI16X1.5OR	M16 x 1.5	21	17.5	8	9.1			
VSTI18X1.5OR	M18 x 1.5	23	19	8	9.1			
VSTI22X1.5OR	M22 x 1.5	27	20	10	9.1			
VSTI27X2OR	M27 x 2	32	23.5	12	5.8			
VSTI33X2OR	M33 x 2	38	25	14	5.8			
VSTI42X2OR	M42 x 2	48	25.5	22	5.8			

* SAE J2244-4 is a draft standard

TUBE FITTING PART #	END SIZE		D (mm)	L (mm)	S6 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 THREAD					CF	71	MS
VSTI10X1ED	M10 x 1		14	12	5	5.8	5.8	
VSTI12X1.5ED	M12 x 1.5		17	17	6	5.8	5.8	
VSTI14X1.5ED	M14 x 1.5		19	17	6	5.8	5.8	
VSTI16X1.5ED	M16 x 1.5		22	17	8	5.8	5.8	
VSTI18X1.5ED	M18 x 1.5		24	17	8	5.8	5.8	
VSTI20X1.5ED	M20 x 1.5		26	19	10	5.8		
VSTI22X1.5ED	M22 x 1.5		27	19	10	5.8		
VSTI26X1.5ED	M26 x 1.5		32	21	12	5.8		
VSTI27X2ED	M27 x 2		32	21	12	5.8		
VSTI33X2ED	M33 x 2		40	22.5	17	5.8		
VSTI42X2ED	M42 x 2		50	22.5	22	4.5		
VSTI48X2ED	M48 x 2		55	22.5	24	4.5		


Dimensions and pressures for reference only, subject to change.

VSTI R-ED

BSPP Hollow Hex Plug


BSPP-ED

(for ISO 1179-1 / DIN 3852-2 Port)

**P47OMN**

Hex Head Plug

BSPP-ORB




TUBE FITTING PART #	END SIZE 1 BSPP				STANDARD Dynamic Pressure (x 1,000 PSI)			CF	71	MS
		D (mm)	L (mm)	S6 (mm)						
VSTI1/8ED	G 1/8 A	14	12	5	5.8	5.8				
VSTI1/4ED	G 1/4 A	19	17	6	5.8	5.8				
VSTI3/8ED	G 3/8 A	22	17	8	5.8	5.8				
VSTI1/2ED	G 1/2 A	27	19	10	5.8	5.8				
VSTI3/4ED	G 3/4 A	32	21	12	5.8	5.8				
VSTI1ED	G 1 A	40	22.5	17	5.8	5.8				
VSTI1 1/4ED	G 1 1/4 A	50	22.5	22	4.5	4.5				
VSTI1 1/2ED	G 1 1/2 A	55	22.5	24	4.5	4.5				

TUBE FITTING PART #	END SIZE 1 BSPP				STANDARD Dynamic Pressure (x 1,000 PSI)			-S	-SS	-B
		H HEX (mm)	L (mm)							
4P47OMN	1/4-19	19	19.1					5.0		
P6P47OMN	3/8-19	22	20.0					5.0		
8P47OMN	1/2-14	27	24.1					5.0		
M14P87OMN	3/4-14	36	26.9					4.0		
M16P87OMN	1-11	41	31.0					3.0		

HP3M

Hex Head Pipe Plug

BSPT



TUBE FITTING PART #	END SIZE 1 BSPT				STANDARD Dynamic Pressure (x 1,000 PSI)			-S	-SS	-B
		C HEX (mm)	L (mm)							
1/8 HP3M	1/8-28	10	14.2		6.0					
1/4 HP3M	1/4-19	14	19.1		6.0					
3/8 HP3M	3/8-19	17	19.8		6.0					
1/2 HP3M	1/2-14	22	24.6		6.0					
3/4 HP3M	3/4-14	27	26.9		5.5					
1 HP3M	1-11	36	31.8		4.5					

Dimensions and pressures for reference only, subject to change.