

## WEST MICHIGAN RUBBER & SUPPLY 1.800.533.9677 sales@westmichiganrubber.com

## **SUVF DUCTING HOSE**

Temperature Range: -20°F to 150°F

Construction: High strength fiber reinforced PVC hose cover bonded to coated spring steel wire

**Standard Color:** Grey

**Standard Lengths:** 25' (3" and 4"), 50'

Size Range: 1-1/4" to 4"

**Description:** 

 Great for industrial and commercial vacuum cleaners and ventilating or cooling industrial machinery

Ideal for bilge pumps and bilge ventilation

Flexibility for easy handling and installation

Other colors and lengths available with minimum order

• Screw on end fittings available



I.D.	Working Pressure	Vacuum	CL Bend Radius	Compression Ratio	O.D. Nominal	Wall Thickness	Wt (lbs/	Part #
(in)	(PSI)	(inHg)	(in)		(in)	(in)	ft)	0.0.4
1.25	45	27	.88	1 ft/6 in	1.50	.032	.31	SUVF0125
1.5	36	26	1.12	1 ft/6 in	1.75	.032	.375	SUVF0150
2	26	25	1.63	1 ft/6 in	2.35	.032	.57	SUVF0200
2.5	20	24	2.19	1 ft/6 in	2.85	.032	.75	SUVF0250
3	20	24	2.48	1 ft/5 in	3.40	.032	.85	SUVF0300
4	14	18	3.26	1 ft/5 in	4.40	.032	.938	SUVF0400

Pressure and vacuum data based on straight lengths of hose at ambient temperature of 72°F.