


WEST MICHIGAN RUBBER & SUPPLY 1.800.533.9677 sales@westmichiganrubber.com

T455LL - 150 PSI Food Discharge Hose



APPLICATION

Discharge of liquid, fatty and oily foods and alcoholic beverages. Hose may be sterilized with 30 PSI steam at 266°F for 30 minutes <u>maximum</u> – open end only.

★ Not recommended for dry abrasive materials.

COVER

White NBR/PVC blend — abrasion, ozone and oil resistant.

REINFORCEMENT

High tensile textile cords.

TUBE

White NBR. Meets FDA and 3A requirements.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C).

STANDARD LENGTH

100 feet

BRANDING

ALFAGOMMA – ITALY T455 10 BAR (150 PSI) – GENERAL PURPOSE FOOD TRANSFER (in black letters)

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT.	MAX. REC.
	(in.)	(mm)	(in.)	(mm)	lbs./100 ft.	WP (PSI)
T455LL150	1 1/2	38	1.89	48	58	150
T455LL200	2	51	2.48	63	93	150
T455LL300	3	76	3.46	88	136	150