



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

T720LG - Material Handling Hose

FDA Grade



APPLICATION

Suction or discharge of wet or dry abrasive materials. Designed for grains, flour and pellet transfer.

COVER

Green SBR/EPDM blend — abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords, with 4 highly flexible steel helix wires and static wire.

TUBE

3/16" white NR — abrasion resistant.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

STANDARD LENGTH

100 feet: 2" through 4"

20 feet: 5", 6" and 8"

50 feet: 4", 5" and 6"

WORKING PRESSURE

See chart below.

BRANDING

ALFAGOMMA – ITALY T720 – BULK FOOD & MATERIAL
– S & D (in white letters)

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T720LG200	2	51	2.64	67	122	150	6
T720LG300	3	76	3.62	92	188	150	9
T720LG400	4	102	4.65	118	256	150	12
T720LG500	5	127	5.71	145	379	75	20
T720LG600	6	152	6.69	170	466	75	24
T720LG800	8	203	8.78	223	701	75	32

★ Please note: Proper grounding of static wire will prolong tube life.