



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

UFD-AP DUCTING HOSE

Temperature Range: -40°F to 200°F

Construction: All thermoplastic polyether polyurethane reinforced with an ABS helix

Standard Color: clear with safety yellow helix

Standard Lengths: 25', 50'

Size Range: 1-1/2" to 8"

Description:

- Smooth interior
- Lightweight and highly flexible
- Suitable replacement for thicker walled EPDM hoses
- The clarity of the hose allows the user to check for blockages
- Helix provides added durability in applications where the hose is being dragged
- Great for dust collection, leaf and woodchip collection or transferring stones, pellets and scrap
- Supplemental helix available



I.D. (in)	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in)	Compression Ratio	O.D. Nominal (in)	Wall Thickness (in)	Wt (lbs/ ft)	Part #
4.0	30	22	4.00	1 ft/6 in	4.53	.033	.55	UFDAP0400
6.0	25	10	6.50	1 ft/6 in	6.61	.035	.93	UFDAP0600
8.0	25	9	9.00	1 ft/6 in	8.74	.035	1.55	UFDAP0800

Pressure and vacuum data based on straight lengths of hose at ambient temperature of 72°F.