



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

## VAC DUCTING HOSE

**Temperature Range:** -40°F to 140°F

**Construction:** All polyethylene hose engineered for optimum strength and flexibility

**Standard Color:** Grey

**Standard Lengths:** 25', 50'

**Size Range:** 1-1/2" and 2"

**Description:**

- Excellent flexing characteristics
- Lightweight and durable
- Ideal for most industrial vacuum applications
- Smooth interior offers unrestricted vacuum, even when the hose is subject to tight bends
- Screw-on cuffs, straight screw-on cuffs, and connectors available



<b>I.D. (in)</b>	<b>Working Pressure (PSI)</b>	<b>Vacuum (inHg)</b>	<b>CL Bend Radius (in)</b>	<b>Compression Ratio</b>	<b>O.D. Nominal (in)</b>	<b>Wall Thickness (in)</b>	<b>Wt (lbs/ ft)</b>	<b>Part #</b>
1.5	20	29	6.10	1 ft/1 ft	1.90	.042	.27	VACHOSE150
2.0	20	29	7.52	1 ft/1 ft	2.48	.048	.38	VACHOSE200

Pressure and vacuum data based on straight lengths of hose at ambient temperature of 72°F.