



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

## NEOPRENE SHEET RUBBER

### General Properties of Neoprene<sup>†</sup>

- Good weather-resistance
- Moderate resistance to petroleum-based fluids
- Good physical properties.

<sup>†</sup> Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

### SPECIFICATIONS:

Commercial grade black neoprene sheet, available in four styles:

Style N40: 40 Duro hardness (Shore Durometer A)

Style N50: 50 Duro hardness (Shore Durometer A)

Style N60: 60 Duro hardness (Shore Durometer A)

Style N70: 70 Duro hardness (Shore Durometer A)

Polymer: Chloroprene

Common Name: Neoprene

ISO/ASTM Designation: CR

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (PSI)	Elongation (%)	Finish
N40	D 2000 M2BC 407	-20°F to +180°F	35 - 45	900	400%	Plate
N50	D 2000 M2BC 507	-20°F to +180°F	45 - 55	1,000	400%	Plate
N60	D 2000 M2BC 607	-20°F to +180°F	55 - 65	1,000	350%	Plate
N70	D 2000 M2BC 707	-20°F to +180°F	65 - 75	1,000	350%	Plate

## Neoprene Sheet Rubber – Page 2

Item Number	Gauge x Width (Inches)	Avg. Length (Linear Ft./Roll)	Approx. Wt./Roll
N40-02 x 36 x 67	1/16" x 36"	67 ft.	96 lbs.
N40-04 x 36 x 67	1/8" x 36"	67 ft.	195 lbs.
N40-06 x 36 x 36	3/16" x 36"	36 ft.	158 lbs.
N40-08 x 36 x 36	1/4" x 36"	36 ft.	210 lbs.
N50-02 x 48 x 67	1/16" x 48"	67 ft.	132 lbs.
N50-04 x 48 x 36	1/8" x 48"	36 ft.	142 lbs.
N50-06 x 48 x 36	3/16" x 48"	36 ft.	213 lbs.
N50-08 x 48 x 18	1/4" x 48"	18 ft.	142 lbs.
N60-01 x 36 x 67	1/32" x 36"	67 ft.	52 lbs.
N60-02 x 36 x 67	1/16" x 36"	67 ft.	99 lbs.
* N60-02 x 36 x 100	1/16" x 36"	100 ft.	147 lbs.
N60-03 x 36 x 67	3/32" x 36"	67 ft.	149 lbs.
N60-04 x 36 x 67	1/8" x 36"	67 ft.	198 lbs.
* N60-04 x 36 x 100	1/8" x 36"	100 ft.	295 lbs.
N60-06 x 36 x 36	3/16" x 36"	36 ft.	161 lbs.
* N60-06 x 36 x 40	3/16" x 36"	40 ft.	179 lbs.
* N60-06 x 36 x 50	3/16" x 36"	50 ft.	223 lbs.
N60-08 x 36 x 36	1/4" x 36"	36 ft.	214 lbs.
* N60-08 x 36 x 40	1/4" x 36"	40 ft.	238 lbs.
* N60-08 x 36 x 50	1/4" x 36"	50 ft.	297 lbs.
N60-12 x 36 x 18	3/8" x 36"	18 ft.	160 lbs.
N60-16 x 36 x 18	1/2" x 36"	18 ft.	214 lbs.
N60-24 x 36 x 18	3/4" x 36"	18 ft.	319 lbs.
N60-32 x 36 x 18	1" x 36"	18 ft.	426 lbs.
N60-02 x 48 x 67	1/16" x 48"	67 ft.	132 lbs.
* N60-02 x 48 x 100	1/16" x 48"	100 ft.	197 lbs.
N60-03 x 48 x 67	3/32" x 48"	67 ft.	200 lbs.
N60-04 x 48 x 36	1/8" x 48"	36 ft.	142 lbs.
* N60-04 x 48 x 50	1/8" x 48"	50 ft.	197 lbs.
N60-06 x 48 x 36	3/16" x 48"	36 ft.	213 lbs.
* N60-06 x 48 x 40	3/16" x 48"	40 ft.	236 lbs.
* N60-06 x 48 x 50	3/16" x 48"	50 ft.	296 lbs.
N60-08 x 48 x 18	1/4" x 48"	18 ft.	142 lbs.
* N60-08 x 48 x 40	1/4" x 48"	40 ft.	316 lbs.
* N60-08 x 48 x 50	1/4" x 48"	50 ft.	394 lbs.
N60-12 x 48 x 18	3/8" x 48"	18 ft.	213 lbs.
* N60-12 x 48 x 30	3/8" x 48"	30 ft.	355 lbs.
N60-16 x 48 x 18	1/2" x 48"	18 ft.	284 lbs.
* N60-16 x 48 x 25	1/2" x 48"	25 ft.	394 lbs.
N60-24 x 48 x 18	3/4" x 48"	18 ft.	425 lbs.
N60-32 x 48 x 18	1" x 48"	18 ft.	567 lbs.
N70-02 x 48 x 67	1/16" x 48"	67 ft.	132 lbs.
N70-04 x 48 x 36	1/8" x 48"	36 ft.	142 lbs.
N70-06 x 48 x 36	3/16" x 48"	36 ft.	213 lbs.
N70-08 x 48 x 18	1/4" x 48"	18 ft.	142 lbs.