



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

351TC

Hydraulic – **'TOUGH COVER**

Constant Working Pressure

351ST

Hydraulic – **SUPER TOUGH**

Constant Working Pressure



# Part Number											
	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	Parkrimp 43 Series
351TC/ST-4	1/4	6,3	.51	13	4000	28	2	50	0.20	0,30	•
351TC/ST-6	3/8	10	.67	17	4000	28	2-1/2	65	0.28	0,42	•
351TC/ST-8	1/2	12,5	.80	20	4000	28	3-1/2	90	0.35	0,52	•
351TC/ST-10	5/8	16	.93	24	4000	28	4	100	0.44	0,66	•
351TC/ST-12	3/4	19	1.09	28	4000	28	4-3/4	120	0.58	0,86	•

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Synthetic rubber.

Reinforcement: Two braids steel wire.

Cover: Synthetic rubber abrasion resistant, MSHA accepted.

Temperature Range: -40°F to +212°F (-40°C to +100°C).

Fittings: 43 Series - pg. B-27.