



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

422

Hydraulic Worldwide

ISO 1436-1 TYPE 1SN/SAE 100R1 TYPE AT / EN 853 TYPE 1SN



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parker 43 Series	Field Attachable 42 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m		
422-4	1/4	6,3	0.53	13	3250	22,5	4	100	0.16	0,24	•	•
422-5	5/16	8	0.59	15	3125	21,5	4-1/2	115	0.18	0,27	•	•
422-6	3/8	10	0.68	17	2600	18,0	5	130	0.23	0,34	•	•
422-8	1/2	12,5	0.81	21	2325	16,0	7	180	0.29	0,43	•	•
422-10	5/8	16	0.94	24	1875	13,0	8	200	0.33	0,49	•	•
422-12	3/4	19	1.09	28	1525	10,5	9-1/2	240	0.42	0,63	•	•
422-16	1	25	1.41	36	1275	8,8	12	300	0.63	0,94	•	•
422-20	1-1/4	31,5	1.79	45	900	6,3	16-1/2	420	0.8	1,19	•	
422-24	1-1/2	38	2	51	725	5,0	20	500	1	1,49	•	
422-32	2	51	2.54	64	575	4,0	25	630	1.5	2,24	•	

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Nitrile.

Reinforcement: One braid steel wire.

Cover: Synthetic rubber.

Temperature Range: -40°F to +212°F (-40°C to +100°C).

Fittings: 43 Series - pg. B-27.
42 Series - pg. B-159.