



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

801 PUSH-LOK Plus

Multipurpose

Available Cover Colors: GRA RED YEL BLU GRN BLK



| # Part Number | Hose I.D. | | Hose O.D. | | Working Pressure | | Minimum Bend Radius | | Weight | | Parkrimp | Field Attachable |
|---------------------|-----------|------|-----------|------|---------------------|-----|------------------------|-----|--------|------|-----------|---------------------|
| | inch | mm | inch | mm | psi | MPa | inch | mm | lbs/ft | kg/m | HY Series | 82 Series |
| 801-4 | 1/4 | 6,3 | 0.50 | 12,7 | 350 | 2,4 | 2-1/2 | 65 | 0.09 | 0,13 | • | • |
| 801-6 | 3/8 | 10 | 0.63 | 15,9 | 350 | 2,4 | 3 | 75 | 0.11 | 0,16 | • | • |
| 801-8 | 1/2 | 12,5 | 0.78 | 19,8 | 300 | 2,1 | 5 | 125 | 0.18 | 0,27 | • | • |
| 801-10 | 5/8 | 16 | 0.91 | 23,0 | 300 | 2,1 | 6 | 150 | 0.19 | 0,28 | • | • |
| 801-12 | 3/4 | 19 | 1.03 | 26,2 | 300 | 2,1 | 7 | 180 | 0.24 | 0,36 | • | • |
| 801-16 | 1 | 25 | 1.28 | 32,6 | 200 | 1,4 | 10 | 250 | 0.37 | 0,55 | • | • |

Application: Pneumatic, petroleum base hydraulic fluid, lubricating oils and antifreeze solutions.

Diesel fuel - approved only when coupled with HY Series fittings.

Inner Tube: Synthetic rubber.

Reinforcement: One fiber braid.

Cover: Synthetic rubber, MSHA accepted

Temperature Range:

Air: +158°F (+70°C)

Water: +185°F (+85°C)

Oil: -40°F to 257°F

(-40°C to +125°C).

Fittings: 82 Series & HY Series.