



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

## CWC FLEXHAUST NEOPRENE DUCTING HOSE

### Features & Benefits

- **Double-ply construction** – works extremely well in both positive and negative pressure applications. Offers extreme flexibility and compressibility, combined with excellent crush-resistance and tensile strength. Recommended for all air handling applications, dust and fume control and light material handling.
- **Neoprene coating with polyester fabric construction** – provides excellent flexibility and will not rot.
- **Manufactured to meet UL94V-O rating.**
- **Standard packaging** – 25' lengths in cartons.



**Service Temperature Range: -65°F (-54°C) to +250°F (+127°C)**

<b>Neo-Duct Double Ply, Wire-Reinforced Flexible Fabric Ducting Hose</b>						
<b>Part #</b>	<b>Nominal Size ID</b>		<b>Min. Bending Radius</b>		<b>Max. W.P. PSI</b>	<b>Hose Weight (lbs/ft)</b>
	<b>(in)</b>	<b>(mm)</b>	<b>(in)</b>	<b>(mm)</b>		
FLX0150	1-1/2	38.1	2.6	66.0	32	.16
FLX0200	2	50.8	3.5	88.9	30	.22
FLX0250	2-1/2	63.5	4.0	101.6	28	.28
FLX0300	3	76.2	5.0	127.0	25	.33
FLX0350	3-1/2	88.9	5.7	144.8	24	.42
FLX0400	4	101.6	6.5	165.1	23	.48
FLX0500	5	127.0	7.5	190.5	22	.61
FLX0600	6	152.4	9.0	228.6	21	.70
FLX0700	7	177.8	9.5	241.3	20	.92
FLX0800	8	203.2	10.0	254.0	19	1.04
FLX1000	10	254.0	11.0	279.4	18	1.36
FLX1200	12	304.8	13.5	342.9	17	1.85
FLX1400	14	355.6	15.5	393.7	16	2.10
FLX1600	16	406.4	18.5	469.9	15	2.40
FLX1800	18	475.2	22.0	558.8	6	2.70
FLX2000	20	508.0	24.0	609.6	4	3.00