



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

T629AA - 150 PSI Black Biofuel Petroleum Suction Hose



APPLICATION

For suction and discharge applications in truck and tank car transfer of gasoline, oil and Biofuels - up to E98 and B100* with up to 60% aromatic content at ambient temperature.

COVER

Black specially-blended neoprene - added resistance against abrasion, ozone and hydrocarbons.

REINFORCEMENT

High tensile textile cords and steel helix wires.

TUBE

Black conductive synthetic rubber.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

STANDARD LENGTH

100 feet: 3/4" through 4"

WORKING PRESSURE

Constant Pressure 150 PSI

BRANDING

ALFAGOMMA – ITALY T629 – 10 BAR (150 PSI)
BIOFUEL (in green letters)

*Applies to Biodiesels which meet the ASTM D6751 criteria

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MIN. BEND RADIUS (In.)
	(In.)	(mm)	(In.)	(mm)		
T629AA075	3/4	19	1.14	29	41	3
T629AA100	1	25	1.38	35	51	4
T629AA125	1 1/4	32	1.65	42	60	5
T629AA150	1 1/2	38	1.89	48	70	6
T629AA200	2	51	2.40	61	91	8
T629AA250	2 1/2	63	2.95	75	142	10
T629AA300	3	76	3.46	88	169	12
T629AA400	4	102	4.57	116	234	16

★ T629 is not recommended for use on a reel.