



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

# **T614AA - 150 PSI Hot Tar & Asphalt Suction & Delivery Hose**



## **APPLICATION**

Hot tar and asphalt suction and delivery service.

## **COVER**

Black CSM — abrasion, ozone and hot tar resistant.

## **REINFORCEMENT**

High tensile textile cords with steel helix wires.

## **TUBE**

Black NBR — hot tar and asphalt resistant.

## **TEMPERATURE RANGE**

-4°F (-20°C) to 356°F (+180°C)

## **WORKING PRESSURE**

10 Bar (150 PSI)

## **STANDARD LENGTH**

100 feet

## **BRANDING**

ALFAGOMMA – ITALY T614 10 BAR (150 PSI) HOT TAR AND ASPHALT (on red stripe)

## **Nominal Specifications**

| <b>SERIES NO.</b> | <b>NOMINAL ID</b> |             | <b>NOMINAL OD</b> |             | <b>WALL THICKNESS (mm)</b> | <b>APPROX. WT. lbs./100 ft.</b> | <b>MIN. BEND RADIUS (in.)</b> |
|-------------------|-------------------|-------------|-------------------|-------------|----------------------------|---------------------------------|-------------------------------|
|                   | <b>(in.)</b>      | <b>(mm)</b> | <b>(in.)</b>      | <b>(mm)</b> |                            |                                 |                               |
| T614AA200         | 2                 | 51          | 2.72              | 69          | 9                          | 151                             | 10                            |
| T614AA300         | 3                 | 76          | 3.78              | 96          | 10                         | 250                             | 15                            |
| T614AA400         | 4                 | 102         | 4.80              | 122         | 10                         | 334                             | 20                            |