



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

T653AA - Soft Wall Marine Exhaust Hose SAE J2006 R1

APPLICATION

Fuel, oil, bilge and water discharge applications.

COVER

Black NBR/PVC blend — abrasion, ozone and hydrocarbon resistant.

REINFORCEMENT

High tensile textile cords.

TUBE

Black NBR



TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+100°C)

STANDARD LENGTH

12½ feet in straight lengths

BRANDING

ALFAGOMMA – ITALY – T653 SOFTWALL MARINE WET
EXHAUST SAE J2006 R1 <SIZE> <YYYY MFG> (in blue
letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)
	(in.)	(mm)	(in.)	(mm)		
T653AA100	1	25	1.38	35	40	75
T653AA112	1 1/8	28	1.50	38	44	75
T653AA125	1 1/4	32	1.65	42	49	75
T653AA137	1 3/8	35	1.77	45	53	75
T653AA150	1 1/2	38	1.89	48	57	75
T653AA162	1 5/8	42	2.05	52	63	75
T653AA175	1 3/4	45	2.17	55	67	75
T653AA189	1 7/8	48	2.28	58	71	75
T653AA200	2	51	2.48	63	91	75
T653AA225	2 1/4	57	2.72	69	101	75
T653AA238	2 3/8	60	2.91	74	124	75
T653AA250	2 1/2	63	3.03	77	130	75
T653AA300	3	76	3.54	90	155	75
T653AA350	3 1/2	90	4.09	104	185	75
T653AA400	4	102	4.57	116	206	75
T653AA450	4 1/2	115	5.08	129	231	75
T653AA500	5	127	5.55	141	254	75
T653AA600	6	152	6.54	168	310	75
T653AA662	6 5/8	168	7.24	184	339	75
T653AA800	8	203	8.70	221	471	75