



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

MILL DISCHARGE HOSES

Single Jacket & Double Jacket "Contractor Grade" Hoses



Applications:

- Pump water discharge • Construction pumps.
- Wash down service on ships and in factories • Plant clean-up

Construction:

- Single or double jacket with all synthetic yarn. Water and mildew-resistant cover, will not rot, even if the hose is stored wet.

Features & Benefits:

- **Easy Identification** - White cover with single stripe. Red stripe indicates single jacket; blue stripe indicates double jacket.
- **Smooth natural rubber tube** - Provides strength and flexibility.
- **Double Jacket version** - Provides greater abrasion resistance.
- **Wide range of operating temperatures** - Hose may be used in temperatures from -25° F (-31° C) to 185° F (+85° C) without stiffening.
- **Packaging/ storage** - Individually packed in cartons for ease of handling and shipping. Hose coils easily for storage.

Nominal Specifications

SERIES NO.	SIZE (In.) (mm)		HOSE ID (In.) (mm)		MAX. WORKING PRESSURE (PSI)	COUPLING BOWL SIZE (In.)	APPROX. WEIGHT PER 100 FT. (lbs.)	STANDARD LENGTH IN CARTON (ft.)
SJMD 150X100	1 1/2	38.1	1.57	40.0	150	1 11/16"	14	100*
SJMD 200X100	2	50.8	2.09	53.0	150	2 1/4"	20	100*
SJMD 250X100	2 1/2	63.5	2.60	66.0	150	2 3/4"	26	100*
SJMD 300X100	3	76.2	3.11	79.0	150	3 1/4"	32	100*
SJMD 400X100	4	101.6	4.06	103.0	150	4 9/32"	50	100*
DJMD 150X100	1 1/2	38.1	1.54	39.0	200	1 13/16"	22	100*
DJMD 250X100	2 1/2	63.5	2.54	64.5	200	2 13/16"	44	100*

Service Temperature: -25° F (-31° C) to 185° F (+85° C) **Note:** Not Intended for use as a fire hose.