




WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

PALADIN PETROLEUM HOSE

APPLICATION:

Designed as a lightweight and flexible hose to transfer gasoline and other petroleum products under pressure, gravity flow or medium suction (up to 23" Hg) at ambient temperatures. Maximum aromatic content 70%. Outer PVC helix provides abrasion resistance and low coefficient of friction. With Antistatic wire (low resistance).



CONSTRUCTION:

TUBE: Black Nitrile synthetic rubber (static dissipating)

COVER: Black Chemivic® synthetic rubber with Orange Pliovic® outer helix

REINFORCEMENT: Synthetic fabric plies

TEMPERATURE: -40°F to 160°F (-40°C to 71°C)

PACKAGING: 100' lengths, coiled and bagel pack

BRANDING: Example: "Goodyear Paladin Drop Hose (Date Code) Made in Canada."

COUPLINGS: Use Goodyear's Insta-Lock Cam & Groove Fittings with this product. See page 220 for available Insta-Lock products.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 543-227

NOM. ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m.
2	50.8	2.87	72.9	150	1.03	2	51	23	584	1.04	1.55
3	76.2	3.92	99.6	150	1.03	3	76	23	584	1.58	2.35
4	101.6	4.85	123.2	75	0.52	5	127	23	584	1.94	2.89

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2010 Veyance Technologies, Inc. All Rights Reserved.