



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

# T253AA - 150 PSI EPDM Layflat Water Discharge Hose



## APPLICATION

High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation.

## COVER

Black abrasion and ozone-resistant EPDM rubber.

## REINFORCEMENT

High tensile textile cords.

## TUBE

Black EPDM rubber.

## TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

## STANDARD LENGTH

100 feet: 1 1/2" through 10"

50 feet: 6", 8" 10" & 12"

## WORKING PRESSURE

150 PSI constant (10 Bar)

## BRANDING

ALFAGOMMA – ITALY – T253 10 BAR (150 PSI) EPDM  
WATER DISCHARGE (in green letters)

## Nominal Specifications

• NOT FOR CHEMICAL APPLICATIONS

| SERIES NO. | NOMINAL ID |      | NOMINAL OD |      | APPROX. WT.<br>lbs./100 ft. | MAX. REC.<br>WP (PSI) |
|------------|------------|------|------------|------|-----------------------------|-----------------------|
|            | (in.)      | (mm) | (in.)      | (mm) |                             |                       |
| T253AA150  | 1 1/2      | 38   | 1.81       | 46   | 36                          | 150                   |
| T253AA200  | 2          | 51   | 2.32       | 59   | 49                          | 150                   |
| T253AA250  | 2 1/2      | 63   | 2.80       | 71   | 60                          | 150                   |
| T253AA300  | 3          | 76   | 3.31       | 84   | 86                          | 150                   |
| T253AA400  | 4          | 102  | 4.33       | 110  | 119                         | 150                   |
| T253AA600  | 6          | 152  | 6.38       | 162  | 200                         | 150                   |
| *T253AA662 | 6 5/8      | 168  | 7.01       | 178  | 217                         | 150                   |
| T253AA800  | 8          | 203  | 8.46       | 215  | 288                         | 150                   |
| T253AA1000 | 10         | 254  | 10.63      | 270  | 512                         | 150                   |
| T253AA1200 | 12         | 305  | 12.56      | 319  | 534                         | 150                   |

## COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.